

PRESERVATIVE PAINT COMPANY -- L-4681 GREEN TT-E-508 #24525 -- 8010-00-597-8194

=====  
Product Identification  
=====

Product ID:L-4681 GREEN TT-E-508 #24525  
MSDS Date:01/01/1985  
FSC:8010  
NIIN:00-597-8194  
MSDS Number: BFHCJ  
=== Responsible Party ===  
Company Name:PRESERVATIVE PAINT COMPANY  
Address:5410 AIRPORT WAY S  
Box:80387  
City:SEATTLE  
State:WA  
ZIP:98108-1726  
Country:US  
CAGE:86589  
=== Contractor Identification ===  
Company Name:PRESERVATIVE PAINT CO  
Address:5410 AIRPORT WAY S  
Box:80387  
City:SEATTLE  
State:WA  
ZIP:98108-1726  
Country:US  
CAGE:86589

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PIGMENTS  
Fraction by Wt: 47%

Ingred Name:ALKYD (SOLIDS)  
Fraction by Wt: 25%

Ingred Name:STANDARD OIL 350B  
Fraction by Wt: 28%

Ingred Name:PARAFFINS(INCL.NAPHTHENES) AROMATICS\*  
Fraction by Wt: 97+3%

=====  
Hazards Identification  
=====

Effects of Overexposure:INHALATION OF HIGH CONCENTRATION OF VAPORS OR MIST MAY LEAD TO ASPHYXIATION PROMPT REMOVAL TO FR.AIR

=====  
First Aid Measures  
=====

First Aid:IN CASE OF SKIN CONTACT,WASH SKIN THOROUGHLY WITH SOAP AND WATER.REMOVE CONTAMINATED CLOTHING AND WASH BEFORE REFUSE.EYE CONTACT.FLUSH EYES WITH WATER AT LEAST 15 MINUTES:IF IRRITATION PERSISTS GET ME DICAL ATTENTION.IN CASE OF SWALLOWING,CALL PHYSIC

=====  
Fire Fighting Measures  
=====

Flash Point:104F TCC 40C  
Lower Limits:0.8  
Upper Limits:6.8  
Extinguishing Media:CO2 DRY CHEMICAL/TURN OFF IGNITION  
Fire Fighting Procedures:CO2 DRY CHEMICAL

=====  
Accidental Release Measures  
=====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION IN VICINITY OF SPILL OR RELEASED VAPORS.CLEAN UP SPILLS AS SOON AS POSSIBLE.

=====  
Handling and Storage  
=====

Handling and Storage  
Precautions:STORE IN COOL WELL-VENTILATED AREA AWAY FROM SOURCES OF IGNITION.CONTAINERS OF THIS MATERIAL SHOULD HAVE A COMBUSTIBLE LIQUID "CAUTION LABEL"

=====  
Exposure Controls/Personal Protection  
=====

Respiratory Protection:ORGANIC VAPOR RESPIRATOR OR GASMASKS;PREFEREABLE SELF-CNTND BR.EQP  
Ventilation:YES,IF CONCENTRATION OF VAPOR IS IN EXCESS  
Protective Gloves:NEOPRENE OR RUB  
Eye Protection:SAFETY GOGGLES  
Supplemental Safety and Health

=====

Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-386

Vapor Pres:0.3

Vapor Density:4.8

Spec Gravity:1.38

Evaporation Rate & Reference:0.12

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PAINTY ODOR

Percent Volatiles by Volume:48.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

MAY REACT WITH STRONG OXIDIZING MATERIALS

Hazardous Decomposition Products:NORMAL COMBUSTION-CARBON DIOXIDE AND

WATER VAP.-INCOMPL-CARB

===== Disposal Considerations =====

Waste Disposal Methods:ABOSRB LARGE SPILLS WITH CLAY DISTOMACCOUS EARTH

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.