

WOOD-KOTE PRODUCTS INC FRMLY SP-DE-WAY PROD. -- OIL STAIN, WOOD, INTERIOR --
8010-00-597-8225

=====
===== Product Identification =====

Product ID:OIL STAIN, WOOD, INTERIOR

MSDS Date:01/01/1985

FSC:8010

NIIN:00-597-8225

MSDS Number: BFHCX

=== Responsible Party ===

Company Name:WOOD-KOTE PRODUCTS INC FRMLY SP-DE-WAY PROD.

Address:8000 N.E. 14TH PLACE

City:PORTLAND

State:OR

ZIP:97217

Country:US

Info Phone

Num:503-285-8371

Emergency Phone Num:1-800-535-5053

CAGE:33429

=== Contractor Identification ===

Company Name:WOOD-KOTE PRODUCTS INC FRMLY SP-DE-WAY PROD.

Address:8000 N.E. 14TH PLACE

Box:City:PORTLAND

State:OR

ZIP:97217

Country:US

Phone:1-800-535-5053

CAGE:33429

=====
===== Composition/Information on Ingredients =====

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 10.1%

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:BENTONE

Fraction by

Wt: 1.2%

Ingred Name:LINSEED OIL

CAS:8001-26-1

RTECS #:OI9690000

Fraction by Wt: 22.7%

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 64.5%

OSHA PEL:100 PPM

Ingred Name:DRIERS

Fraction by Wt: 1.4%

=====
Hazards Identification
=====

Effects of Overexposure:INH MAY LEAD TO ASPHIXIATION IF IN LG
PROPORTION

=====
First Aid Measures
=====

First Aid:IF INGESTED DO NOT I
NDUCE VOMIT, CALL MD. EYES: FLUSH
W/WATER. SKIN: SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:101F, 38.3C PMCC
Extinguishing Media:CO2, DRY POWDER

=====
Accidental Release Measures
=====

Spill Release Procedures:EXTINGUISH ALL SOURCES OF IGNITION, CLEAN UP
W/CLAY, DIATOMACEOUS EARTH. AVOID PROLONGED CNTCT & BRTHNG OF
VAPORS.

=====
Exposure Controls/Personal Protection
=====

Ventilati

on:LOCAL EXHST
Protective Gloves:GLOVES
Eye Protection:CHEM SAFETY GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:320F, 160C
Vapor Pres:002
Vapor Density:1.15
Spec Gravity:0.9300
Evaporation Rate & Reference:0.22 BUAC
Solubility in Water:NEGLIGIBLE
Appearance and Odor:DARK BROWN LIQ, MILD ODOR
Percent Volatiles by Volume:77.0

===== Stability and Reactivity Data =====

STRONG
OXIDIZERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.