

AMERON INDUSTRIAL COATINGS DIVISION -- YELLOW #13594 -- 8010-00-597-8229

=====  
Product Identification  
=====

Product ID:YELLOW #13594

MSDS Date:01/01/1987

FSC:8010

NIIN:00-597-8229

MSDS Number: BFHDB

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

City:BREA

State:CA

ZIP:92621-3904

Country:US

Info Phone Num:714-529-4597

Emergency Phone Num:714-529-45

97

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Address:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====  
Composition/Information on Ingredients  
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 41.6%

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR

1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-

6  
RTECS #:GB2975000  
Fraction by Wt: 0.5%  
OSHA PEL:0.05 MG/M3 (PB)  
ACGIH TLV:0.05MG/M3(CR)A2;8990

=====  
Hazards Identification  
=====

Effects of Overexposure:ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE  
NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====  
First Aid Measures  
=====

First Aid:IN CASE OF CONTACT-FLUSH SKIN AND EYES WITH WATER AND REMOVE  
CONTAMINATED CLOTHING. IF INHALED-REMOVE TO FRESH AIR. CALL A  
PHYSICIAN IF CONDITIONS PERSIST.

=====  
Fire Fighting Measures  
=====

Flash Point:85F TCC  
Lower Limits:1.1  
Extinguishing Media:SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE  
FIRES-FOAM  
Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN  
Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXPLODE

=====  
Accidental Release Measures  
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITI  
ON. AVOID  
BREATHING VAPORS. REMOVE INERT ABSORBENT AND NON-SPARKING TOOLS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE  
FLAMMABLES.  
Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID  
FREE-FALL OF LIQUID IN EXCESS OF A FEW INCHES.

=====  
Exposure Controls/Personal Protection  
=====

Respirato

ry Protection:USE NIOSH APPROVED PAINT RESPIRATOR OR AIR  
SUPPLIED RESPIRATOR

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST AS NECESSARY

Supplemental Safety and Health

RESPIRATOR USE BASED ON CHEM CONC. AND CONDITION OF USE.

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:311-373F

Vapor Density:>1

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:60.1

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRE, HEAT AND HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND  
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department  
of Defense. The United States of Ame

rica in no manner whatsoever,

expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.