

OCTAGON PROCESS INC. -- VV-L-825A AM 2 TYPE II;LUBRICATING OIL -- 9150-00-598-2911
===== Product Identification =====

Product ID:VV-L-825A AM 2 TYPE II;LUBRICATING OIL

MSDS Date:06/07/1989

FSC:9150

NIIN:00-598-2911

MSDS Number: BFHFC

=== Responsible Party ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

City:EDGEWATER

State:NJ

ZIP:07020

Info Phone Num:201-945-9400

Emergency Phone Num:

201-945-9400

CAGE:82925

=== Contractor Identification ===

Company Name:OCTAGON PROCESS INC.

Address:596 RIVER ROAD

Box:City:EDGEWATER

State:NJ

ZIP:07020

Country:US

Phone:201-945-9400

CAGE:82925

===== Composition/Information on Ingredients =====

Ingred Name:PETROLEUM LUBE OIL

OSHA PEL:5 MG/CUM,AS OIL MIST

ACGIH TLV:5 MG/CUM,AS OIL MIST

Ingred Name:ADDITIVES MIXTURE (PER SPEC-TYPE NOT SPECIFIED)

===== Hazards Identification =====

Reports of

Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:ACUTE:IRRITATING TO EYES,SKIN,MUCOUS MEMBRANES,COUGHING. CHRONIC:IRRITATION.

Explanation of Carcinogenicity:PER MSDS DATA.

Effects of Overexposure:NONE NOTED BY MANUFACTURER. LOW TOXICITY AND LOW HAZARD TO HEALTH.

Medical Cond Aggravated by Exposure:NO DATA AVAILABLE.

=====
===== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH W/SOAP&WATER. RMV CONTAM CLTHG&SHOES. INGEST:INDUCE VOMIT. RPT UNTIL VOMIT IS C LEAR. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

=====
===== Fire Fighting Measures =====

Flash Point:350F,177C

Extinguishing Media:CO*2,ALC.FOAM

Fire Fighting Procedures:NO WATER ON MATL. WATER SPRAY TO ABSORB VAPOR/COOL CONT.

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====
=====

Spill Release Procedures:REMOVE IGNITION SOURCES,VENTILATE AREA WELL.ABSORB WITH VERMICULITE OR OTHER MATERIALS, SUCH AS SAWDUST,RAGS,PAPER & PLACE IN CLOSED CONTAINER. USE NON SPARKING TOOLS. WEAR PROPER PROTECTIVE EQUIPMENT DURING CLEAN UP.

=====
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL,DRY WELL VENTED LOW FIRE RISK AREA. PROTECT FROM HEAT,SHOCK,FRICITION. KEEP CONTAINERS CLOSED.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NORMALLY NOT NEEDED;USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE PEL/TLV OR SCBA IN AN ENCLOSED AREA.

Ventilation:LOCAL EXHAUST TO ELIMINATE MISTS/FUMES/GASES.

Protective Gloves:RUBBER

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:AS REQUIRED TO PREVENT PROLONGED CONTACT.

Work Hygienic Practices:WASH HANDS BEFORE EATING,DRINKING OR USING TOILET FACILITIES.

Supplem

ental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:V6

Boiling Pt:B.P. Text:575F,302C

Spec Gravity:0.97

Solubility in Water:NEGLIGIBLE

Appearance and Odor:AMBERED COLORED LIQ,CHARACTERISTIC PETROL.ODOR.

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

NONE SPECIFIED

Stability Condition to Avoid:HEAT,IGNITION SOURCES

Hazardous Decomposition Products:INCOMPLETELY BURNED CARBON PRODUCTS,

CO*2, CO.

=====
Disposal Considerations
=====

Waste Disposal Methods:INCINERATE IN APPROVED INCINERATOR OR DISPOSE OF
IN APPROVED CHEMICAL DUMP IN ACCORDANCE WITH LOCAL,STATE & FEDERAL
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this informati
on to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.