

PRATT AND LAMBERT INC -- ENAMEL ALKYD LUST BLUE 35044 -- 8010-00-598-5148

=====
Product Identification
=====

Product ID:ENAMEL ALKYD LUST BLUE 35044

MSDS Date:01/01/1985

FSC:8010

NIIN:00-598-5148

MSDS Number: BFHFV

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency Phone Num

:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 35%

ACGIH TLV:500 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION

OF RESPIRATORY
TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

=====
First Aid Measures
=====

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING
CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL
PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:104F, 40C
Lower Limits:1.10
Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE
FIRES
Fire Fighting
Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE
AVAILABLE
Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION. AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE WITH INERT ABSORBENT AND
NON-SPARKING TOOLS.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE
QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106
Other Precautions:GROUND CONTAINERS WHEN POURING.AVOID FREE FALL OF
LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATER
MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE
VENTILATION

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:OPEN AREA:BUR MINES MECH RESPIRATOR;CLOSED:BUR
MINES CHEM/MECH FILTE
Ventilation:GENERAL DILUTION OR LOCAL EXHAUST TO

KEEP TLV BELOW LIMIT

Protective Gloves:REQ IF LONG CON

Eye Protection:TO PROTECT VS SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO
CONTAMINATED CLOTHING.

Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311-373F

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:61

===== Stability and Reactivity Data =====

Stabili

ty Indicator/Materials to Avoid:YES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implie

d, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.