ASHLAND OIL INC. -- TECTYL 437 -- 8030-00-598-5915
==================== Product Identification =====================

Product ID:TECTYL 437
MSDS Date:01/01/1987
FSC:8030
NIIN:00-598-5915
MSDS Number: BFHKR
=== Responsible Party ===
Company Name:ASHLAND OIL INC.
Emergency Phone Num:614-790-3333
CAGE:81355
=== Contractor Identification ===
Company Name:ASHLAND INC
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:4111
4
Country:US
Phone:800-622-6846
CAGE:81355

============= Composition/Information on Ingredients =============

Ingred Name:2000 PALE OIL
Fraction by Wt: >60%
ACGIH TLV:5MG/CUM

==================== Hazards Identification =====================

Effects of Overexposure:EYES-CAN CAUSE SEVERE
   IRRITAT,REDNESS,TEARING,BLURRED VISION.EXCESS VAP CAN CAUS
   ASPHYXI,UNCONSCIOUS

====================== First Aid Measures =======================

First Aid:SKIN:THOROUGHLY WASH EXPOSED AREA W/

SOAP & WATER.LAUNDER &
   REMOV CONTAMINAT CLOTHES.FLUSH EYES W/LG AMTS OF WATER.IF
   SWALLOWED,GIVE 2 GLASSES OF WATER;INDUCE VOMITING IMMED.BY STICKING
   FINGER DOWN THR OAT.CALL DR BREATHED-REMOV TO FRESH AIR.

==================== Fire Fighting Measures =====================

Flash Point:460F 238C
Extinguishing Media:DRY CHEM,CARBON DIOXIDE
Fire Fighting Procedures:SELF-CONTAIN BREATHING APPARATUS W/A FULL
   FACEPIECE OPER(SUP

================= Accidental Release Measures =====
============

Spill Release Procedures:SMALL-ABSORB LIQUID ON PAPER,VERMICULITE,FLOOR
   ABSORB,OTHER ABSORB MATERIAL & TRANSFER TO HOOD.LG SPILL-PERSONS
   NOT WEARING PROTECTIVE EQUIPMT SHLD BE EXCLUD FR AREA OF SPILL
   UNTIL CLEANUP HAS BEEN CO MPLETED.STOP SILL AT SOURCE.

===================== Handling and Storage =====================

Handling and Storage Precautions:CONTAINERS OF THIS MATERIAL MAY BE
   HAZARDOUS WHEN EMPTIED.SINCE EMPTIES(CONTAINERS)RETAIN PRODUCT
   RESIDUE(V
AP,LIQUID &/OR SOLID)ALL HAZ PRECAUT,OBSERV

============= Exposure Controls/Personal Protection =============

Respiratory Protection:NIOSH/MSHA APPRVD SELF-CONTAIN BREATHING APPARAT
   IF TLV IS EXCEEDED
Ventilation:SUFFICIENT MECH/LOC EXHAUST TO KP EXPOSURE BELOW TLV.
Protective Gloves:BUNA-N,NEOPRENE
Eye Protection:SAFETY GLASSES
Other Protective Equipment:TO PREVENT REPEATED/PROLONG SKN CONTACT,WR
   IMPERVIOUS CLOTHN
Supplemental Safety and Health

================= Physical/Chemical
 Properties ==================

HCC:N1
Boiling Pt:B.P. Text:UNK
Spec Gravity: