

UNION CHEMICALS DIV,UNION OIL COMPANY OF CALIFORNI -- AMSCO SOLV 1420,XYLENE --
6810-00-598-6600

===== Product Identification =====

Product ID:AMSCO SOLV 1420,XYLENE

MSDS Date:01/01/1987

FSC:6810

NIIN:00-598-6600

MSDS Number: BFHMD

=== Responsible Party ===

Company Name:UNION CHEMICALS DIV,UNION OIL COMPANY OF CALIFORNI

Address:1650 EAST GOLF ROAD

City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Inf

o Phone Num:312-619-2644

Emergency Phone Num:312-619-2644

CAGE:DO714

=== Contractor Identification ===

Company Name:UNION CHEMICALS DIVISION

Address:1345 NORTH MEACHAM ROAD

Box:7600

City:SCHAUMBURG

State:IL

ZIP:60196

Phone:213-664-2121 OR 800-424-9300

CAGE:DO714

Company Name:UNION OIL CO OF CALIFORNIA, CORP. DIV-EASTERN

Address:1650 EAST GOLF ROAD

Box:City:SCHAUMBURG

State:IL

ZIP:60195

Country:US

Phone:708-619-2644

CAGE:77416

===== Composition/Information on Ingredients =====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

Fraction by Wt: >98%.

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:MAY IRRITATE EYES & SKIN,RESPIRATORY TRACT IRRITATION,LIVER & KIDNEY DAMAGE IN HUMANS,NAUSEA & VOMIT

=====
===== First Aid Measures =====

First Aid:INHALE:REMOVE T

O FRESH AIR, GIVE CPR/O*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH;
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER
SYMPTOMS OF OVEREXPOSURE.

=====
===== Fire Fighting Measures =====

Flash Point:20-100F

Lower Limits:UNKN

Upper Limits:UNKN

Extinguishing Media:USE FOAM,CO*2, OR DRY CHEMICALS

Fire Fighting Procedures:USE SCBA APPROVED BY NIOSH/MSHA FOR
FIRE-FIGHTING.

Unusual Fire/Explosion Hazard:KEEP WORK AREA

S FREE OF HOT METAL

SURFACES & OTHER SOURCES OF IGNITION.

=====
===== Accidental Release Measures =====

Spill Release Procedures:KEEP SOURCES OF IGNITION & HOT METAL SURFACE
ISOLATED FROM THE SPILL.FLUSH SPILLED MATERIAL INTO SUITABLE
RETAINING AREAS OR CONTAINERS.SMALL AMOUNTS OF SPILLED MATERIAL MAY
BE ABSORBED INTO AN APPROP RIATE ABSORBANT.

=====
===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODU

CT CONTAINERS COOL, DRY, AND

AWAY FROM SOURCES OF IGNITION. PROVIDE ADEQUATE VENTILATION.

Other Precautions: DO NOT INHALE VAPORS. AVOID SKIN & EYES CONTACT. DO NOT SMOKE IN WORK AREAS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS

Ventilation: PROVIDE MECHAN(GEN/LOCAL EXHAUST) VENT TO MAINTN 1.0

Spec Gravity: