

PRATT AND LAMBERT INC -- ENAMEL ALKYD GLOSS FIRE RED 12199 -- 8010-00-598-7211

=====  
Product Identification  
=====

Product ID:ENAMEL ALKYD GLOSS FIRE RED 12199

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-7211

MSDS Number: BFHMP

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153

City:WICHITA

State:KS

ZIP:67201

Country:US

Info Phone Num:316-733-1361

Emergency

Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====  
Composition/Information on Ingredients  
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

ACGIH TLV:100PPM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)

CAS:1330-20-7

RTECS #:ZE2100000

OSHA PEL:100 PPM/150 STEL

ACGIH TLV:100 PPM/150STEL;9192

EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:CADMIUM COMPOUNDS  
RTECS #:EV0260000  
ACGIH TLV:0.05MG/CUMTR

Ingred Name:CADMIUM SELENIDE SULFIDE  
CAS:12626-36-7  
RTECS #:EV2350000  
ACGIH TLV:0.05MG/CUMTR

===== Hazards Identification =====

Effects of Overexposure:PNEUMOCONIOSIS,PERMANENT NERVOUS SYSTEM  
DAMAGE,INTERNAL ORGAN DAMAGE.DELIBERATE INHALATION HARMFUL.

===== First Aid Measures =====

First Aid:INGESTION:G  
ET IMMEDIATE MEDICAL ATTENTION.INHALATION:REMOVE  
TO FRESH AIR.RESTORE BREATHING.KEEP WARM AND QUIET.CONSULT  
PHYSICIAN.EYES:15 MINUTE WATER FLUSH.CONSULT PHYSICIAN.SKIN:REMOVE  
CONTAMINATED C LOTHING.WASH SKIN WITH SOAP AND WATER.

===== Fire Fighting Measures =====

Flash Point:80F,27C  
Extinguishing Media:CARBON DIOXIDE,DRY CHEMICALS,ALCOHOL,POLYMER FOAMS.  
Fire Fighting Procedures:SELF CONTAINED BREATHING APPAR.WATER-FOG TO  
COOL CONTAINERS.  
Unusua  
I Fire/Explosion Hazard:CONTAINER EXPLOSION HAZARD DUE TO EXTREME  
HEAT,EXPOSURE TO SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.CONTAIN WITH INERT  
MATERIAL.TRANSFER TO COVERED METAL CONTAINERS.PREVENT ENTRY TO  
DRAINS,SEWERS AND GROUND WATER,WEAR RESPIRATORS,EYE,SKIN  
PROTECTION.REMOVE LIQUID WITH INER T ABSORBENT AND NON-SPARKING  
TOOLS.

===== Handling and Storage

=====  
Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE  
QUANTITIES IN COMPLIANCE WITH OSHA 29CFR1910.106.CLOSE CONTAINER  
AFTER USE.DO NOT BREATHE FUMES,SANDING PARTICLES.

Other Precautions:DO NOT WELD,CUT OR BRAZE EMPTY CONTAINER.DO NOT CLEAN  
AND RE-USE CONTAINER.DO NOT USE PRESSURE TO EMPTY CONTAINER.GROUND  
AND BOND CONTAINER TO RECEIVING VESSEL.

=====  
Exposure Controls/Personal Protection

Ventilation:LOCAL VENTILA  
TION/EXHAUST TO REMOVE DECOMPOSITION  
BYPRODUCTS

Protective Gloves:SOLVENT RESIST.

Eye Protection:FACE SHIELD;SHIELDED SPEC

Supplemental Safety and Health

=====  
Physical/Chemical Properties

HCC:F3

Boiling Pt:B.P. Text:244F,118C

Vapor Density:>AIR

Evaporation Rate & Reference:SLOWER THAN ETHER

Percent Volatiles by Volume:62

=====  
Stability and Reactivity Data

Stability Indicator/Materials to Avoid:YES

STRONG ACIDS,ALKALI

NES,OXIDIZERS.

Stability Condition to Avoid:EXCESSIVE HEAT.SOURCES OF IGNITION.

Hazardous Decomposition Products:CO,CO\*2,SMOKE FROM IGNITION

=====  
Disposal Considerations

Waste Disposal Methods:DO NOT INCINERATE CLOSED CONTAINERS.DISPOSE OF  
IN ACCORDANCE WITH EPA,LOCAL,STATE AND FEDERAL REGULATIONS FOR  
FLAMMABLE,HAZARDOUS WASTES.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elem

ents of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.