

PRATT AND LAMBERT INC -- FIRE RED 12199 -- 8010-00-598-7211

=====
Product Identification
=====

Product ID:FIRE RED 12199

MSDS Date:01/01/1987

FSC:8010

NIIN:00-598-7211

MSDS Number: BFHMQ

=== Responsible Party ===

Company Name:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=== Contractor Identification ===

Company Name:PRATT AND LAMBER

T INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 40-5%

OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION:ANESTHETIC,IRRITATION OF THE
RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACT

=====

===== First Aid Measures =====

First Aid:IN CASE OF CONTACT,FLUSH SKIN AND EYES WITH PLENTY OF WATER WHILE REMOVING CONTAMINATED CLOTHING.IF INHALED,REMOVE TO FRESH AIR.CALL A DR. IF SYMPTOMS PERSIST.

===== Fire Fighting Measures =====

Flash Point:104F TCC

Lower Limits:1.10

Extinguishing Media:USE NATIONAL FIRE PROTECTION ASSOC.(NFPA) CLASS B EXTINGUISH

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE FOR FI

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED.ISOLATE FROM HEAT,ELECTRICAL EQUIPMENT,SPARKS AND OPEN FLAME.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES,HOT SURFACES,AND ELECTRICAL,STATIC,OR FRICTIONAL SPARKS)AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F.STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106.

Other Precautions:CONTAINERS SHOULD BE GROUNDED WHEN POURING.AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES.DO NOT FLAME CUT,BRAZE OR WELD COATED MATERIAL WITHOUT BUREAU OF MINES APPROVED RESPIRATOR OR APP

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN OUTDOOR OR OPEN AREAS,USE BUREAU OF MINES

APPROVED MECHANICAL FIL

Ventilation:PROVIDE GENERAL DILUTION OR LOCAL EXHAUST VENTILATION IN VOL

Protective Gloves:REQUIRED FOR PR

Eye Protection:USE SAFETY EYEWEAR DESIGN

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.

Supplemental Safety and Health

INHALATION:ANESTHETIC,IRRITATION OF THE RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION CHARACTERIZED BY HEADACHE,DIZZINESS,STAGGERING GAIT,CONFUSION,UNCONSCIOUSNESS OR COMA.SKIN

OR EYE CO

===== Physical/Chemical Properties =====

HCC:F4

Boiling Pt:B.P. Text:311TO 373F

Percent Volatiles by Volume:64

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AVOID FIRES,HEAT,AND HOT SURFACES.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE,AND

FEDERAL REGULATIONS.INCINERATE I

N APPROVED FACILITY.DO NOT

INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.