

PRATT & LAMBERT-WICHITA DIV. -- 793-448 -- 8010-00-616-0018

=====  
Product Identification  
=====

Product ID:793-448

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-0018

MSDS Number: BFHXW

=== Responsible Party ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Emergency Phone Num:316-733-1361

CAGE:KO010

=== Contractor Identification ===

Company Name:PRATT & LAMBERT-WICHITA DIV.

Box:2153

CAGE:KO010

Company Nam

e:PRATT AND LAMBERT INC

Address:945 BURLINGTON

Box:206

City:KANSAS CITY

State:MO

ZIP:64141

Country:US

CAGE:92216

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ISOBUTYL ACETATE (SARA III)

CAS:110-19-0

RTECS #:AI4025000

Fraction by Wt: 25.0%

OSHA PEL:150 PPM

ACGIH TLV:150 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ingred Name:ISOBUTYL ALCOHOL (SARA III)

CAS:78-83-1

RTECS #:NP9625000

Fraction by Wt: 8.0%

OSHA PEL:100 PPM

ACGIH TLV:50 PPM; 9293

EPA Rp

t Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:ALIPHATIC NAPHTHA  
RTECS #:SE7525000  
Fraction by Wt: 15.0%  
ACGIH TLV:200 PPM

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)  
CAS:78-93-3  
RTECS #:EL6475000  
Fraction by Wt: 15.0%  
OSHA PEL:200 PPM/300 STEL  
ACGIH TLV:200 PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)  
CAS:8030-30-6  
RTECS #:SE7555000  
Fraction by Wt: 8.0%  
OSHA PEL:100 PPM

=====  
Hazards Identif  
ication =====

Effects of Overexposure:INAL:ANESTHETIC & IRRIT. TO AIRWAY;  
EYE/SKIN:IRRIT. HEADACHE,DIZZY,COMA

=====  
First Aid Measures =====

First Aid:SKIN/EYE: FLUSH WITH PLENTY OF WATER WHILE REMOVING  
CONTAMINATED CLOTHING. INHALED:REMOVE TO FRESH AIR. CALL MD. IF  
SYMPTOMS PERSISTS.

=====  
Fire Fighting Measures =====

Flash Point:13 F, -11 C, TCC  
Lower Limits:0.9  
Extinguishing Media:CARBON

DIOXIDE/DRY CHEM.SMALL;POLYMER FOAM-LARGE  
FIRE

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS AVAILABLE  
FOR FIREMEN

Unusual Fire/Explosion Hazard:CLOSED CONTAINERS EXPOSED TO HEAT MAY  
EXOLODE DUE TO PRESSURE BUILD-UP,USE H\*2O TO COOL CLOSED CANS.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAME,HOT  
SURFACES,& ELECTRICAL,STATIC, OR FRICTIONAL SPARKS).AVOID BREATHING  
VAPORS. VENTILA  
TE AREA. REMOVE WITH INERT ABSORBENT AND  
NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F. STORE LARGE  
AMTS. IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS  
ONE FLAMMABLE (OR COMBUSTIBLE) LIQUID.

Other Precautions:DO NOT TAKE INTERNALLY,CONTAINERS SHOULD BE GROUNDED  
WHEN POURING,AVOID FREE FALL IN EXCESS OF A FEW INCHES, DO NOT  
FLAME CUT,BRAZE,OR WELD COATED MATERIA  
L WITHOUT VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:APPROVED BUREAU OF MINES RESPIRATORS W/PROPER  
FILTER OR HOOD

Ventilation:GENERAL DILUTION/LOCAL EXHAUST FOR TLV&LEL SAFETY & WELDING

Protective Gloves:ALOT OF CONTACT

Eye Protection:YES, IF SPLASHING

Other Protective Equipment:PREVENT PROLONGED SKIN CONTACT TO  
CONTAMINATED CLOTHING

Supplemental Safety and Health

BOILING RANGE 79-143 C, CELLOSOLVE ACETATE