

AMERON INDUSTRIAL COATINGS DIVISION -- RED #11105 -- 8010-00-616-7486

=====
Product Identification
=====

Product ID:RED #11105

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-7486

MSDS Number: BFHYC

=== Responsible Party ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Emergency Phone Num:316-733-1361

CAGE:09869

=== Contractor Identification ===

Company Name:AMERON INDUSTRIAL COATINGS DIVISION

Addr

ess:201 N BERRY ST

Box:City:BREA

State:CA

ZIP:92621-3904

Country:US

Phone:714-529-4597

CAGE:09869

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 50.0%

OSHA PEL:100 PPM

Ingred Name:LEAD CHROMATE (OSHA PEL FOR LEAD FROM 29CFR
1910.1025),(CRO3 CEILING 0.1 MG/M3)

CAS:7758-97-6

RTECS #:GB2975000

Fraction by Wt: 3.0%

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TLV:0.05MG/M3(CR)A2;8990

===

=====
Hazards Identification
=====

Effects of Overexposure: ANESTHETIC, IRR. OF RESPIRATORY TRACT OR ACUTE NERVOUS SYS. DEPRESSION, EYE & SKIN IRRITATION

=====
First Aid Measures
=====

First Aid: IN CASE OF CONTACT FLUSH SKIN AND EYES WITH WATER AND REMOVE CONTAMINATED CLOTHING. IF INHALED REMOVED TO FRESH AIR. CALL A PHYSICIAN IF CONDITIONS PERSIST.

=====
Fire Fighting Measures
=====

=====

Flash Point: 85F TCC

Lower Limits: 1.1

Extinguishing Media: SMALL FIRES-CARBON DIOXIDE OR DRY CHEM. LARGE FIRES-FOAM

Fire Fighting Procedures: SELF-CONTAINED BREATHING APPARATUS FOR FIREMEN

Unusual Fire/Explosion Hazard: CLOSED CONTAINERS EXPOSED TO HEAT MAY EXPLODE

=====
Accidental Release Measures
=====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS. REMOVE WITH INERT ABSORBENT AND NON-SPARKING

=====

Handling and Storage
=====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F. STORE LARGE QUANTITIES IN BUILDINGS DESIGNED FOR STORAGE OF NFPA CLASS ONE FLAMMABLES.

Other Precautions: CONTAINERS SHOULD BE GROUNDED WHEN POURING. AVOID FREE FALL OF LIQUID IN EXCESS OF A FEW INCHES

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection: USE NIOSH APPROVED PAINT RESPIRATOR OR AIR SUPPLIED RESPIRATOR

Ventilation: PROVIDE GEN

ERAL DILUTION OR LOCAL EXHAUST AS NECESSARY
Supplemental Safety and Health
RESPIRATOR USE BASED ON CHEM CON. AND CONDITION OF USE

===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:311-373F
Vapor Density:>1
Evaporation Rate & Reference:SLOWER THAN ETHER
Percent Volatiles by Volume:62.5

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:AVOID FIRE,HEAT AND
HOT SURFACES

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL EGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims
all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.