View NSN Online: https://aerobasegroup.kr/nsn/8010-00-616-7689

PRATT AND LAMBERT INC -- 742426 ENAMEL ALKYD GLOSS GREEN 14158 -- 8010-00-616-7689

Product ID:742426 ENAMEL ALKYD GLOSS GREEN 14158

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-7689

MSDS Number: BFHZS === Responsible Party ===

Company Name: PRATT AND LAMBERT INC

Address:16116 E 13TH ST

Box:2153 City:WICHITA

State:KS ZIP:67201 Country:US

Info Phone Num:316-733-1361

Fm

ergency Phone Num:716-873-6000 DOT EMER 8002553924

CAGE:61196

=== Contractor Identification ===

Company Name: PRATT AND LAMBERT INC

Box:6027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

======= Composition/Information on Ingredients ========

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7 RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST


ACGIH TLV:10 MG/M3 TDUST; 9293

Ingred Name:*MINERAL SPIRITS

CAS:64475-85-0 RTECS #:PY8240000 ACGIH TLV:100PPM

Ingred Name

:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS
Ingred Name:IRON OXIDE CAS:1332-37-2 RTECS #:NO7380000
Ingred Name:CARBON BLACK CAS:1333-86-4 RTECS #:FF5800000 OSHA PEL:3.5 MG/M3 ACGIH TLV:3.5 MG/M3; 9192
============ Hazards Identification ==============
Effects of Overexposure:SWALLOW:GASTROINTESTINALIRRIT, NAUSEA,VOMIT,DIARRHEA.MATRL INTO LUNGS CA N CAUS FATAL PNEUMONITIS
======================================
First Aid:IF SWALLOW:INDUCE VOMITING IMMED BY GIVING 2 GLASSES OF WATR& STICKING FINGR DOWN THROAT.CONSULT DR OR POISON CONTROL CENTR IMMED. (NEVER GIVE ANYTHING BY MOUTH AN UNCONSCIOUS PERSON) INHAL:REMOV TO F RESH AIR IMMEDIATELY.
======================================
Flash Point:80F 27C Extinguishing Media:CL B FIRES:CO*2, DRY CHEMICAL OR ALCOH FOAM. Fir
e Fighting Procedures:SELF-CONTND BREATHING APPARAT. WATR TO COOL EXPOS CONTNRS
Unusual Fire/Explosion Hazard:CONTNRS TIGHTLY CLOS.ISOLAT FR HEAT,ELECTR EQPMT,SPARKS & FLAME.MAY EXPLOD IF EXPOS TO EXTREME HEAT.
========= Accidental Release Measures ===========
Spill Release Procedures:KEEP SPECTATORS AWAYELIMINATE ALL IGNITION SOURCES (FLAMES,HOT SURFACES, & SOURCES OF ELECTRICAL,STATIC OR FRICTIONAL SPARKS).DIKE & CONTAIN SPILL W/INERT MATRL(E.G. SAND,



Waste Disposal Methods:DISPOSE IN ACCORD W/FED. STATE & LOC LAWS.CONTAM ABSORBANT MAY BE D

ISPOS IN EPA-PERMITTED HAZARDOUS WASTE LANDFILLS.
INCINERATE ONLY INEPA PERMITTED FACILITY. DO NOT INCINERATE CLOSED CONTAINERS.OBSER V PRECAUTIONS F/FLAMMABLE MATERIAL DISPOSAL.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its u se. Any person utilizing this

document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.