

ILLINOIS BRONZE POWDER AND PAINT COMPANY -- IB NO 220 -- 8010-00-616-9143

===== Product Identification =====

Product ID:IB NO 220

MSDS Date:01/01/1987

FSC:8010

NIIN:00-616-9143

MSDS Number: BFJBL

=== Responsible Party ===

Company Name:ILLINOIS BRONZE POWDER AND PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Info Phone Num:312-488-8001

Emergency Phon

e Num:800-228-5635

CAGE:91794

=== Contractor Identification ===

Company Name:ILLINOIS BRONZE PAINT COMPANY

Address:300 EAST MAIN STREET

City:LAKE ZURICH

State:IL

ZIP:60047-2580

Country:US

Phone:800-228-5635

CAGE:91794

===== Composition/Information on Ingredients =====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 11.1%

OSHA PEL:100 PPM

Ingred Name:METHYLENE CHLORIDE (SARA III)

CAS:75-09-2

RTECS #:PA8050000

Fraction by Wt: 3

8.7%
OSHA PEL:500 PPM/C,1000; Z2
ACGIH TLV:50 PPM, A2; 9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 1.5%
OSHA PEL:100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION-ANESTHETIC;IRRITATION OF RESPIRATORY TRACT;DIZZINESS.SKIN OR EYE-PRIMARY IRRITATION

=====
First Aid Measures
=====

First Aid:FU
MES-REMOVE FROM EXPOSURE,MOVE TO FRESH AIR.EYES-FLUSH WITH LARGE AMOUNTS OF WATER.FOR AT LEAST 15 MIN. CALL PHYSICIAN.SKIN-WIPE OFF WITH TOWEL.REMOVE REMAINDER WITH MINERAL SPIRITS OR LACQUER REMOVER.WASH WITH SOAP & WATER.

=====
Fire Fighting Measures
=====

Flash Point:-40F,-40C
Lower Limits:1.3%
Extinguishing Media:NFPA CLASS B EXTINGUISHER
Fire Fighting Procedures:WATER TO COOL CONTAINERS WEAR GOGGLES AND BREATHING APPARATU
Unusual Fire/
Explosion Hazard:CANS WILL RUPTURE AT 190F AND DISCHARGE FLAMMABLE CONTENTS

=====
Accidental Release Measures
=====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION.AVOID BREATHING VAPORS.VENTILATE AREA.REMOVE WITH INERT ABSORBENT

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDINGS DESIGNED AND PROTECTED FOR STORAGE OF NFPA CLASS 1A F

LAMMABLE LIQUIDS

Other Precautions:DO NOT SPRAY IN EYES.DO NOT PUNCTURE OR INCINERATE
CANS.DO NOT FLAME CUT,BRAZE OR WELD WITHOUT BUR. OF MINES APPROVED
RESPIRATOR OR APPROPRIATE VENTILATION.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE FOR CASUAL USE
Ventilation:DILUTION OR EXHAUST TO KEEP BELOW TLV
Protective Gloves:NONE
Eye Protection:NO SPECIAL REQUIRED
Supplemental Safety and Health
B.P. RANGE 6-199C

=====
===== Physical/
Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:42-391F
Percent Volatiles by Volume:89

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:HCL,CO,PHOSGENE

=====
===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IN ACCORDANCE WITH LOCAL,STATE AND
FEDERAL REGULATIONS.INCINERATE IN APPROVED FACILITY. DO NOT
INCINERATE CLOSED CONTA
INERS

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular

situation.