

NATIONAL AEROSOL PRODUCTS COMPANY -- AA-1551 GRAY PRIMER -- 8010-00-616-9181
===== Product Identification =====

Product ID:AA-1551 GRAY PRIMER

MSDS Date:01/01/1985

FSC:8010

NIIN:00-616-9181

MSDS Number: BFJBX

=== Responsible Party ===

Company Name:NATIONAL AEROSOL PRODUCTS COMPANY

Emergency Phone Num:(213) 627-2668

CAGE:59986

=== Contractor Identification ===

Company Name:NATIONAL AEROSOL PRODUCT

S CO SUB OF GROW GROUP INC

Address:2193 E 14TH STREET

Box:City:LOS ANGELES

State:CA

ZIP:90021-2843

Country:US

CAGE:59986

===== Composition/Information on Ingredients =====

Ingred Name:NO INGREDIENT FOR THIS FORMULATION_INGREDIENT

===== Hazards Identification =====

Effects of Overexposure:INHALATION: HEADACHE/NAUSEA/DIZZINESS. SKIN:
PROLONGED OR REPEATED CONTACT MAY CAUSE IRRITATION.

===== First Aid Measures =====

=====

First Aid:INHALATION: REMOVE TO FRESH AIR. SKIN: FLUSH WITH LARGE
AMOUNTS OF WATER. REMOVE CONTAMINATED CLOTHING. EYE: FLUSH WITH
CLEAN WATER FOR AT LEAST 15 MINUTES.

===== Fire Fighting Measures =====

Flash Point:58F PMCC

Extinguishing Media:CARBON DIOXIDE, DRY CHEMICAL, FOAM

Fire Fighting Procedures:SELF-CONTAINED BREATHING APPARATUS SHOULD BE
WORN BY FIRES.

Unusual Fire/Explosion Hazard:WATER SHOULD BE USED TO COOL CONTAINER

EXPOSED TO FIRE.

===== Accidental Release Measures =====

Spill Release Procedures:AVOID BREATHING VAPORS, EXTINGUISH IGNITION SOURCES IN IMMEDIATE AREA. AVOID CONTACT WITH LIQUID.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMPERATURES.
Other Precautions:CLOSE CONTAINERS AFTER USE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IN CONFINED AREAS USE US B OR M APPROVED RESPIRATOR DEVICE.

Ventilation:PROVIDE VENTILATION TO KEEP BELOW TLV AND LEL.

Protective Gloves:REQUIRED

Eye Protection:SOLVENT RESISTANT

Other Protective Equipment:NORMAL PROTECTIVE CLOTHING.

Supplemental Safety and Health

2193 EAST 14TH STREET/LOS ANGELES, CA 90021. PRODUCTS ALSO CONTAINS:
BUTANE 25.0% 1000 PPM, VECHILE 23.7%, SOLVENTS 49.0%.

===== Physical/Chemical Properties =====

HCC:V3

Boiling Pt:B.P. Text:176-310F

Va

apor Density:>AIR

Spec Gravity:1.017

Evaporation Rate & Reference:SLOWER THAN ETHER

Solubility in Water:SLIGHT

Appearance and Odor:GRAY MOBILE LIQUID CONTAINING VOLATILE SOLVENTS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZING MATERIALS, RUBBER SOFTENS

Hazardous Decomposition Products:CARBON MONOXIDE, CARBON DIOXIDE

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF

IN CLOSED CONTAINERS AWAY FROM
IGNITION SOURCES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.