

EASTMAN KODAK CO. -- 146 4080 KODAKFIX(OLD FORMULATION) -- 6750-00-619-9943
===== Product Identification =====

Product ID:146 4080 KODAKFIX(OLD FORMULATION)

MSDS Date:12/12/1986

FSC:6750

NIIN:00-619-9943

MSDS Number: BFJJM

=== Responsible Party ===

Company Name:EASTMAN KODAK CO.

Address:343 STATE ST.

City:ROCHESTER

State:NY

ZIP:14650

Emergency Phone Num:716-722-5151

CAGE:19139

=== Contractor Ident

ification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

===== Composition/Information on Ingredients =====

Ingred Name:AMMONIUM THIOSULFATE

CAS:7783-18-8

RTECS #:XN6465000

Fraction by Wt: 30-40%

Other REC Limits:NONE ESTABLISHED

Ingred Name:SODIUM METABISULFITE

CAS:7681-57-4

RTECS #:UX8225000

Fraction by Wt: 5-15%

OSHA PEL:5 MG/M3

ACGIH TLV

:5 MG/M3; 9192

Ingred Name:SODIUM ACETATE
CAS:126-96-5
RTECS #:AJ4375000
Fraction by Wt: 5-10%
Other REC Limits:NONE ESTABLISHED
OSHA PEL:NONE ESTABLISHED
ACGIH TLV:NONE ESTABLISHED

Ingred Name:WATER
CAS:7732-18-5
RTECS #:ZC0110000
Fraction by Wt: 55-65%

=====
Hazards Identification
=====

Routes of Entry: Inhalation:YES Skin:NO Ingestion:NO
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO
Health Hazards Acute and Chronic:SEE "OVEREXPOSURE SYMPTOM"
Effects of Overexposure:NONE NOTED BY MFR. LOW TOXICITY & LOW HAZARD TO HEALTH.

=====
First Aid Measures
=====

First Aid:SKIN:WASH WITH SOAP AND WATER. EYES: FLUSH WITH WATER.
INHALED: REMOVE TO FRESH AIR. REMOVE CONTAMINATED CLOTHING.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:EXTINGUISH WITH AGENT SUITABLE FOR SURROUNDING FIRE
Fire Fighting Procedures:WEAR SCBA & PROTECTIVE CLOTHING TO PREVENT SKIN/EYE CONTACT.
Unusual Fire/Explosion Hazard:FIRE OR EXCESSIVE HEAT MAY CAUSE PRODUCTION OF HAZARDOUS DECOMPOSITION PRODUCTS.

=====
Accidental Release Measures
=====

Spill Release Procedures:WEAR APPROPRIATE PROTECTIVE EQUIPMENTS. STOP LEAK W/O RISK. DIKE LIQUID W/ABSORBENT & TRANSFER LIQ TO SALVAGE TANK. MFR SUGGESTS TO FLUSH MATERIAL TO AN ACID-FREE SEWER WITH LARGE AMOUNTS OF WATER.

=====
Handling and Storage
=====

=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA. PROTECT FROM PHYSICAL DAMAGE.AVOID ANY PHYSICAL CONTACT. KEEP CONTAINERS TIGHTLY CLOSED

Other Precautions:NONE

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE SHOULD BE NEEDED

Ventilation:MECHANICAL (GENERAL)

Protective Gloves:AS REQUIRED

Eye Protection:SAFETY GLASSES

Other Protective Equipment:NONE SHOULD BE NEEDED,BUT GOOD HYGIENE PRACTICE BE FO

LLOWED

Supplemental Safety and Health

THIS PRODUCT HAS A KODAK'S SOLUTION NUMBER 4247. THIS IS AN OLD FORMULATION. THE NEW FORMULATION CAN BE FOUND UNDER P/N IND:B, AND IT HAS A KODAK SOLUTION NUMBER 5385.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:18

Vapor Density:0.6

Spec Gravity:1.28

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS SOLUTION,AMMONIA ODOR

Percent Volatiles by Volume:55

=====

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

NONE

Stability Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:THERMAL DECOMPOSITION WILL EMIT OXIDES OF SULFUR & NITROGEN

===== Disposal Considerations =====

Waste Disposal Methods:MANUFACTURER STATES THAT DISCHARGE, TREATMENT OR DISPOSAL MAY BE SUBJECT TO FEDERAL, STATE OR LOCAL LAWS.

Disclaimer (provided with this information by the

compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.