

J.W.HARRIS CO.,INC. -- NICKEL 55 ELECTRODE -- 3439-00-640-2351

=====
Product Identification
=====

Product ID:NICKEL 55 ELECTRODE

MSDS Date:11/01/1985

FSC:3439

NIIN:00-640-2351

MSDS Number: BFJRY

=== Responsible Party ===

Company Name:J.W.HARRIS CO.,INC.

Address:10930 DEERFIELD ROAD

City:CINCINNATI

State:OH

ZIP:45242

Country:US

Emergency Phone Num:513-891-2000

CAGE:27911

=== Contractor Identificati

on ===

Company Name:J. W. HARRIS CO., INC.

Address:10930 DEERFIELD ROAD

Box:City:CINCINNATI

State:OH

ZIP:45242-4110

Country:US

Phone:513-891-2000

CAGE:27911

=====
Composition/Information on Ingredients
=====

Ingred Name:NICKEL (SARA III)

CAS:7440-02-0

RTECS #:QR5950000

Fraction by Wt: 53%.

OSHA PEL:1 MG/M3

ACGIH TLV:1 MG/M3; 9192

Ingred Name:IRON OXIDE

CAS:1309-37-1

RTECS #:NO7400000

Fraction by Wt: 44.5%

OSHA PEL:10 MG/M3 (FE)

ACGIH TLV:5 MG/M3(FE),B2; 9293

Ingred Name:SI

LICA, CRYSTALLINE - FUSED
CAS:60676-86-0
RTECS #:VV7328000
Fraction by Wt: 0.5%
OSHA PEL:SEE TABLE Z3
ACGIH TLV:0.1 MG/M3 RDUST;9293

Ingred Name:COPPER (SARA III)
CAS:7440-50-8
RTECS #:GL5325000
Fraction by Wt: 0.1%
OSHA PEL:0.1MG/M3 FUME/1 DUST
ACGIH TLV:0.2MG/M3 FUME; 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:MANGANESE (SARA III)
CAS:7439-96-5
RTECS #:OO9275000
Fraction by Wt: 0.3%
OSHA PEL:(C) 5 MG/M3 DUST
ACGIH TLV:5 MG/M3 DUST 9293

Ingred Name:GRAPHITE, SYNTHETIC
CAS:7
440-44-0
RTECS #:FF5250100
Fraction by Wt: 1.5%
OSHA PEL:15 MG/M3 TDUST
ACGIH TLV:2 MG/M3 TDUST; 9293

Ingred Name:SULFUR
CAS:7704-34-9
RTECS #:WS4250000
OSHA PEL:5 MG/CUM (SO*2)
ACGIH TLV:2 MG/CUM (SO*2)

=====
===== Hazards Identification =====

Effects of Overexposure:INHL:DIZZ,NAUS,URI IRRIT,WELD FUME FEVER-
BODY:ACHE,CHILLS,FEVER.WELDING ARC:POSS EYE & SKN BURNS.

=====
===== First Aid Measures =====

First Aid:REMOVE TO FRESH A

IR, GIVE ART RESP OR OXYGEN AS REQD. CALL
PHYSICIAN IMMED.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:AS REQD FOR NEARBY FIRE
Fire Fighting Procedures:AS REQD FOR NEARBY FIRE
Unusual Fire/Explosion Hazard:WELDING ARC CAN IGNITE COMBUSTIBLES.

=====
Handling and Storage
=====

Handling and Storage Precautions:DO NOT TOUCH LIVE ELECTRICAL PARTS OF
WELDING GEAR,INSULATE BODY FROM WORK & GROUN
D.
Other Precautions:PROVIDE PROTECTIVE SCREENS, FLASH GOGGLES TO NEARBY
WORKERS AS REQD.AVOID DIRECT EYE,SKIN EXPOSURE TO WELD ARC.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE DUST,FUME RESPIRATOR AS REQD
Ventilation:LOCAL EXHAUST, WELDING BOOTH
Protective Gloves:WELDERS GLOVES
Eye Protection:WELD MASK W/FILTER LENS
Other Protective Equipment:USE HEAD,BODY PROTECTION AS
REQD,APRON,HAT,SHOULDER PROTEC
Supplemental Safety and Health
MSD
S #21783 NON-STD DATED NOV 85.ADDED INGREDIENT:(6)
CHROMIUM(VI),(FLUX COATING),TLV= 0.05 MG(CRVI)/CUM.HUMAN CARCINOGEN
IARC,NIOSH,NTP,ACGIH.

=====
Physical/Chemical Properties
=====

HCC:N1
Appearance and Odor:SOLID ROD, FLUX COATED

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES
NONE
Stability Condition to Avoid:NONE
Hazardous Decomposition Products:WELD FUMES; CARBON, NITROGEN OXIDES,
OZON

E

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.