

3M COMPANY, ADHESIVE COATING & SEALANT DIV. -- EC-1063 ACCELERATOR -- 8030-00-652-3562
===== Product Identification =====

Product ID:EC-1063 ACCELERATOR

MSDS Date:01/01/1987

FSC:8030

NIIN:00-652-3562

MSDS Number: BFJYD

=== Responsible Party ===

Company Name:3M COMPANY, ADHESIVE COATING & SEALANT DIV.

Address:3M CENTER

City:ST. PAUL

State:MN

ZIP:55144-1000

Country:US

Info Phone Num:612-733-1110

Em

ergency Phone Num:612-733-1110

CAGE:04963

=== Contractor Identification ===

Company Name:3M MINNESOTA MINING AND MFG CO ADHESIVES SEALERS DIV

Address:3M CTR

Box:City:SAINT PAUL

State:MN

ZIP:55144-1000

Country:US

Phone:800-364-3577/651-737-6501(24 HOURS)

CAGE:04963

===== Composition/Information on Ingredients =====

Ingred Name:LEAD PEROXIDE (LEAD DIOXIDE), (OSHA PEL FROM 29CFR
1910.1025)

CAS:1309-60-0

RTECS #:OG0700000

Fraction by Wt: 50%.

OSHA PEL:0.05 MG/M3 (PB)

ACGIH TL

V:0.15 MG/M3(PB); 8990

Ingred Name:DIBUTYL PHTHALATE (SARA III)

CAS:84-74-2

RTECS #:TI0875000

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3; 9192

EPA Rpt Qty:10 LBS

DOT Rpt Qty:10 LBS

Ingred Name:STEARIC ACID (COMBINED W/DIBUTYL PHTHALATE.COMPRISES APPROX. 50% OF PRODUCT)

CAS:57-11-4

RTECS #:WI2800000

=====
===== Hazards Identification =====

Effects of Overexposure:CHRONIC EXPOSURE CAN LEAD TO LEAD POISONING.
AVOID EYE & SKIN CONTACT.

=====
===== First
Aid Measures =====

First Aid:EYE: FLUSH W/ PLENTY OF WATER & CALL A PHYSICIAN.

=====
===== Fire Fighting Measures =====

Extinguishing Media:CO*2, FOAM, DRY CHEMICAL

Fire Fighting Procedures:NONE

Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:COLLECT SPILLED MATERIAL USING ABSORBENT MATERIAL. CLEAN UP RESIDUE & AREA.

=====
===== Handling and Storage
=====

Handling and Storage Precautions:AVOID EYE CONTACT 6 PROLONGED SKIN CONTACT. WASH HANDS BEFORE EATING OR SMOKING. LAUNDER CONTAMINATED CLOTHING BEFORE REUSE.

=====
===== Exposure Controls/Personal Protection =====

Ventilation:MFR STATES: MECHANICAL VENTILATION ADEQUATE

Protective Gloves:IMPERV. GLOVES

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

PART B OF TWO PART EC-801 SEALANT KIT.STORE WITH PART A AND DO NOT SEPERATE. ENTRY B

===== Physical/Chemical Properties =====

HCC:F4
Spec Gravity:1.9
Appearance and Odor:DARK BROWN PASTE
Percent Volatiles by Volume:0.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Hazardous Decomposition Products:CO, CO*2, & SMOKE PARTICLES

===== Disposal Considerations =====

Waste Disposal Methods:MFR RECM: LG QTY--DISPOSE IN SECURE LANDFILL AT
HAZARDOUS WASTE MANAGEMENT FACILITY. CONSULT APPROPRIATE FED.,
STATE & LOCAL CODES. SM QTY--DISPOSE OF INDIV EMPTY CONTAINERS IN A
SANITARY LANDFILL IAW FED,. STATE & LOCAL CODES.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.