

TENNECO CHEMICALS,INC. -- O-M-232,METHANOL,METHYL ALCOHOL -- 6810-00-663-9417

=====
Product Identification
=====

Product ID:O-M-232,METHANOL,METHYL ALCOHOL

MSDS Date:01/01/1985

FSC:6810

NIIN:00-663-9417

MSDS Number: BFKGQ

=== Responsible Party ===

Company Name:TENNECO CHEMICALS,INC.

Address:TURNER PL

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Country:US

CAGE:99559

=== Contractor Identification ===

Company Name:TENNECO CHEMICALS INC ORGANIC AND POLYMERS DIV

Address:TURNER PL

Box:365

City:PISCATAWAY

State:NJ

ZIP:08854

Country:US

Phone:908-981-5000

CAGE:99559

=====
Composition/Information on Ingredients
=====

Ingred Name:METHYL ALCOHOL (METHANOL) (SARA III)

CAS:67-56-1

RTECS #:PC1400000

Fraction by Wt: 99.9%

OSHA PEL:S,200PPM/250STEL

ACGIH TLV:S,200PPM/250STEL; 93

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
Hazards Identification
=====

=====

Effects of Overexposure:WEAKNESS,HEADACHE,NAUSEA,VOMITING,ABDOMINAL PAIN,DIMNESS OF VISION,NARCOSIS COMA,RESPIRATORY FAILURE

===== First Aid Measures =====

First Aid:IRRIGATE EYES WITH WATER FOR AT LEAST 15 MINUTES.MOVE TO FRESH AIR,REMOVE CONTAMINATED CLOTHING,WASH BODY WITH SOAP & WATER.INGESTION INDUCE VOMITING,STOMACH WASH IF SWALLOWED WITH 4 % SOLUTION OF SODI UM BICARBONATE.COMBAT SHOCK:OXYGEN,SIMULANTS.

===== F
ire Fighting Measures =====

Flash Point:54F,12C CC
Lower Limits:6.0
Upper Limits:36.5
Extinguishing Media:DRY CHEMICAL,ALCOHOL FOAM,WATER SPRAY INEFFECTIVE
Fire Fighting Procedures:USE WATER TO KEEP FIRE EXPOSED CONTAINERS COOL
Unusual Fire/Explosion Hazard:EXPOSURE TO HEAT BUILDS UP PRESSURE IN
CLOSED DRUMS.COOL WITH WATER.AVOID SPARKS.BULK VESSELS GROUND

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE SOURCES OF IGNITION.VENTILATE AREA.FLUSH AREA WITH WATER SPRAY.

===== Handling and Storage =====

Handling and Storage Precautions:STORE CONTAINERS IN WELL VENTILATED PLACE.LARGE VOLUME STORAGE,REMOTE FROM INHABITED BUILDINGS OR STRUCTURES
Other Precautions:KEEP AWAY FROM ALL SOURCES OF IGNITION.KEEP CONTAINER CLOSED.WEAR CHEMICAL GOGGLES,OR FACE SHIELD,CHEMICAL CARTRIDGE RESPIRATOR,RUBBER GLOVES,APRONS & BOOTS.AVOID BREATHING VAPORS & GET DOCTOR

=====

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS;OR BUREAU OF MINES CARTRIDGE

Ventilation:MECHANICAL AS NEEDED,SPARK PROOF FANS.

Protective Gloves:RUBBER

Eye Protection:SAFETY GOGGLES

Other Protective Equipment:FACE SHIELD,CHEMICAL GOGGLES,APRONS,BOOTS,RESPIRATOR,SHOWER.

Supplemental Safety and Health

THIS COMMODITY IS GRADE "A" IN FEDERAL SPECIFICATION OM232

=====
Physical/Chemical Properties
=====

HCC:F5

Boiling Pt:B.P. Text:148F,65C

Vapor Pres:92

Vapor Density:1.1

Spec Gravity:0.8

Evaporation Rate & Reference:2.0, BUTYL ACETATE

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR,COLORLESS LIQUIDS,SLIGHT ALCOHOL ODOR.

Percent Volatiles by Volume:100

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS,SOURCES OF IGNITION

Stability Condition to Avoid:KEEP AWAY FRM OPEN FLAME,HEAT & SPARKS.

OPEN CONTAINER

Hazardous Decomposition Products:BURNING MAY PRODUCE IRRITATING VAPOR OR CARBON MONOXIDE

=====
Disposal Considerations
=====

Waste Disposal Methods:SPRAY INTO A FURNACE UNDER CONTROLLED PROCEDURES.INCINERATEON WILL DECOME EASIER BY MIXING WITH A MORE FLAMMABLE SOLVENT

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United St

ates of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.