View NSN Online: https://aerobasegroup.kr/nsn/6810-00-664-0271

Product ID:O-C-265, ETHYL ALCOHOL, ABSOLUTE, ACS MSDS Date:01/01/1985 FSC:6810 NIIN:00-664-0271 MSDS Number: BFKHZ === Responsible Party === Company Name: U.S. INDUSTRIAL CHEMICALS CO Address:11500 NORTHLAKE DRIVE Box:429550 City:CINCINNATI State:OH ZIP:45249 Country:US Info Phone Nu m:513-530-6917 Emergency Phone Num:713-479-2873/800-424-9300(CHEMTREC) CAGE:KO791 === Contractor Identification === Company Name: QUANTUM CHEMICAL CORPORATION USI DIVISION Address:11500 NORTHLAKE DRIVE Box:429550 City:CINCINNATI State:OH ZIP:45249 Country:US Phone:713-479-2873/800-424-9300(CHEMTREC) CAGE:78918 Company Name: U.S. INDUSTRIAL CHEMICALS COMPANY Address:11500 NORTHLAKE DRIVE Box:429550 City:CINCINNATI State:OH ZIP:45249 Country:US Phone:513-530-6917 CAGE:KO791

====== Compositio

n/Information on Ingredients =========

Ingred Name:ETHYL ALCOHOL (ETHANOL) CAS:64-17-5 RTECS #:KQ6300000 Fraction by Wt: 92.4% OSHA PEL:1000 PPM ACGIH TLV:1000 PPM; 9192

Ingred Name:WATER CAS:7732-18-5 RTECS #:ZC0110000 Fraction by Wt: 7.6%

Effects of Overexposure: IRRITATION OF EYES & RESPIRATORY TRACT; HEADACHE, DIZZINESS, DROWSINESS, FATIGUE, NAUSEA, TREMOR, NARCOSIS.

First Aid:IRRIGATE EYES WITH WATER.STOMACH WASH,IF SWALLOWED,FOLLOWED BY SALINE CATHARSIS.REMOVE PATIENT FROM EXPOSURE

Flash Point:80F,21.1C TOC Lower Limits:3.3 Upper Limits:19.0 Extinguishing Media:DRY CHEMICAL,FOAM,OR CARBON DIOXIDE.WATER SPRAY INEFFECTIVE Fire Fighting Procedures:WEAR SELF-CNTND BRTHG APP;H*20 SPRAY COOL CONT. Unusual Fire/Explosion Hazard:CONTAINERS MAY EXPLODE IN HEAT OF F IRF.

Spill Release Procedures: EVACUATE UNPROTECTED PERSONS. ELIM IGNITION SOURCES. STOP LEAK. H*20 SPRAY COOL CONT/DIVERT SPILL FROM FIRE/HEAT. PROVIDE VENTILATION. ABSORB W COMMERCIAL ABSORBENT, SHOVEL INTO METAL DRUMS; LG SPILL: DI KE W COMMERCIAL ABSORBENT, PUMP INTO COVERED DRUMS.

Handling and Storage Precautions: STORE AWAY FROM OXIDIZING AGE

Respiratory Protection:SELF CONTAINED BREATHING APPARATUS OR CHEMICAL CARTRIDGE RESPIRATOR. Ventilation:AS REQUIRED TO CONTR L TLV IN AIR. Protective Gloves:RUBBER Eye Protection:CHEMICAL OR SAFETY GOGGLE Other Protective Equipment:RUBBER APRONS,RUBBER BOOTS,SAFETY EYE BATH. Supplemental Safety and Health THE ITEM COMPOSITION IS IN PERCENT BY WEIGHT. THE ITEM IS 190 PROOF ETHYL ALCOHOL

HCC:F2

Boiling Pt:=78.3C, 173.F Vapor Pres:401 Vapor Density:1.59 Spec Gravity:0.8158 Evaporation Rate & amp; Reference:2.7-BUTYL ACETATE Solubility in Water:COMP LETE Appearance and Odor:COLORLESS LIQUID,MILD ALCOHOLIC ODOR. Percent Volatiles by Volume:99.9

Stability Indicator/Materials to Avoid:YES OXIDIZING MATERIALS,PEROXIDES,CHROMIC ACID,NITRIC ACID Stability Condition to Avoid:KEEP AWAY FROM HEAT OR IGNITION SOURCES. Hazardous Decomposition Products:CARBON DIOXIDE

Waste Disposal Methods: KEEP IN COVERED DRUMS, PEN

DING DISPOSAL. HANDLE & DISPOSE IN FULL COMPLIANCE WITH ALL APPLICABLE INTERNATIONAL, FEDERAL, STATE & LOCAL REGULATIONS. MFG SUGGESTS INCINERATION OF LARGE AMOUNTS (MIX WITH MOR E FLAMMABLE SOLVENT); FLUSH RESIDUE W H*20.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.