

PRATT AND LAMBERT -- 741612 ENAMEL ALKYD LUST GRAY 36231 -- 8010-00-664-3365

=====
Product Identification
=====

Product ID:741612 ENAMEL ALKYD LUST GRAY 36231

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-3365

MSDS Number: BFKMW

=== Responsible Party ===

Company Name:PRATT AND LAMBERT

Emergency Phone Num:316-733-1361

CAGE:61196

=== Contractor Identification ===

Company Name:PRATT AND LAMBERT INC

Box:6

027

City:CLEVELAND

State:OH

ZIP:44101-1027

Country:US

Phone:216-566-2902

CAGE:61196

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS

CAS:64475-85-0

RTECS #:PY8240000

Fraction by Wt: 35%

ACGIH TLV:500 PPM

=====
Hazards Identification
=====

Effects of Overexposure:INHALATION-ANESTHETIC,IRRITATION OF RESPIRATORY TRACT OR ACUTE NERVOUS SYSTEM DEPRESSION.

=====
First Aid Measures
=====

First Aid:CONTACT-FLUSH SKIN AND EYES WITH WATER WHILE REMOVING CONTAMINATED CLOTHING. INHALATION-REMOVE TO FRESH AIR. CALL PHYSICIAN IF SYMPTOMS PERSIST.

=====
Fire Fighting Measures
=====

Flash Point:104F, 40C TCC

Lower Limits:1.10

Extinguishing Media:NFPA CLASS B EXTINGUISHER; POLYMER FOAM FOR LARGE FIRES

Fire Fighting Procedures:SELF CONTAINED BREATHING APPARATUS SHOULD BE AVAILABLE

Unusual Fire/Explosion Hazard:KEEP CONTAINED

RS TIGHTLY CLOSED

===== Accidental Release Measures =====

Spill Release Procedures: REMOVE ALL SOURCES OF IGNITION. AVOID BREATHING VAPORS VENTILATE AREA REMOVE WITH INERT ABSORBENT AND NON-SPARKING TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions: DO NOT STORE ABOVE 120F STORE LARGE QUANTITIES IN BUILDING DESIGNED TO COMPLY WITH OSHA 1910.106
Other Precautions: GROUND CONTAINERS WHEN POORING. AVOID FREE FALL OF LIQUID IN XS OF FEW INCHES DO NOT FLAME CUT, BRAZE OR WELD COATED MATERIAL WITHOUT BUR OF MINES APPROVED RESPIRATOR OR APPROPRIATE VENTILATION.

===== Exposure Controls/Personal Protection =====

Respiratory Protection: OPEN AREA BUR MINES MECH RESPIRATOR-CLOSED-BUR MINES CHEM/MECH FILTE
Ventilation: GENERAL DILUTION OR LOCAL EXHAUST TO KEEP TLV BELOW LIMIT.
Protective Gloves: REG IF LONG CON
Eye Protection: TO PROTECT VS SPLASHING
Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT TO CONTAMINATED CLOTHING.
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC: F4
Boiling Pt: B.P. Text: 311-373F
Vapor Density: >AIR
Evaporation Rate & Reference: SLOWER THAN ETHER
Percent Volatiles by Volume: 58

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

===== Disposal Considerations =====

Waste Dis

posal Methods:DISPOSE IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS-INCINERATE IN APPROVED FACILITY-DO NOT
INCINERATE CLOSED CONTAINERS

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.