View NSN Online: https://aerobasegroup.com/nsn/8030-00-664-4968

BAKER SEALANTS & COATINGS CO -- ZINC CHROMATE PUTTY MIL-P-8116 -- 8030-00-664-4968

Product ID:ZINC CHROMATE PUTTY MIL-P-8116

MSDS Date:01/01/1985

FSC:8030

NIIN:00-664-4968

MSDS Number: BFKPX === Responsible Party ===

Company Name: BAKER SEALANTS & COATINGS CO

Emergency Phone Num:201-333-6986

CAGE:FO833

=== Contractor Identification ===
Company Name:BAKER SEALANTS

& COATINGS CO., INC.

Address:234 SUYDAM AVENUE

Box:B

City: JERSEY CITY

State:NJ

ZIP:07304-3306

Phone:(201) 333-6986

CAGE:FO833

Company Name: BAKER SEALANTS AND COATINGS CO

Address:234 SUYDAM AVE Box:City:JERSEY CITY

State:NJ

ZIP:07304-3306 Country:US

Phone:201-333-6986

CAGE:34094

======= Composition/Information on Ingredients ========

Ingred Name: POLYSULFIDE RUBBER

Fraction by Wt: 57%.

Ingred Name:ZINC CHROMATE

CAS:13530-65-9 RTECS #:GB3290000

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0

.01MG/M3(CR)A1;9192 Ingred Name: ASBESTOS (AMIANTHUS, OBSOLETE AMOSITE), (FOR OSHA PEL, SEE 29CFR 1910.1101) CAS:1332-21-4 RTECS #:CI6475000 OSHA PEL:0.2 FIBERS/CC ACGIH TLV:0.5 FIBERS/CC; A1;89 EPA Rpt Qty:1 LB DOT Rpt Qty:1 LB Ingred Name: MERCAPTO BENZYL THIAZYL DISULFIDE, MBTS CAS:120-78-5 RTECS #:DL4550000 Ingred Name: DIPHENYL GUANIDINE, DPG CAS:102-06-7 RTECS #:MF0875000 First Aid:EYE: IMMED FLUSH W/WATER AT LEAST **15 MIN** ============= Fire Fighting Measures ======================== Flash Point:>200F Extinguishing Media: NONFLAMMABLE ============= Accidental Release Measures ================== Spill Release Procedures: NORMAL CLEAN UP PROCEDURES ============= Handling and Storage ================= Handling and Storage Precautions: STORE BETWEEN 40-90F. MFG STATES PROD IS STABLE AND NONFLAMMABLE PASTE, NO VOLATILES. ======= Exposure Controls/Personal Protection = _____ Ventilation:LOCAL EXHAUST, YES Protective Gloves:IF DESIRED Eye Protection: IF DESIRED Supplemental Safety and Health MBTS, DPG, & TETRAMETHYL THIURAM DISULFIDE - METHYL TUADS - COMPRISE 6% OF PROD. ZINC CHROMATE, ASBESTOS, TALC, & CALCIUM CARBONATE MAKE UP PIGMENT PORTION & ARE 37% OF PROD. ======== Physical/Chemical Properties ============= HCC:N1

Spec Gravity: 1.40

Solubility in Water: NEGLIGIBLE

Appearance and Odor:HEAVY PASTE, SLIGHT GASEOUS ODOR

Percen

t volatiles by volume:0
======== Stability and Reactivity Data ===========
Stability Indicator/Materials to Avoid:YES
======== Disposal Considerations ============
Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG.
Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, w arrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.