

CON-LUX COATINGS, INC. -- TT-P-38D PAINT,ALUMINUM READY-MIXED -- 8010-00-664-5678

=====
Product Identification
=====

Product ID:TT-P-38D PAINT,ALUMINUM READY-MIXED

MSDS Date:01/01/1985

FSC:8010

NIIN:00-664-5678

MSDS Number: BFKQG

=== Responsible Party ===

Company Name:CON-LUX COATINGS, INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergency Phone Num:201-287-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 35%

OSHA PEL:100 PPM

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 10%

OSHA

PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
===== Hazards Identification =====

Effects of Overexposure:INHAL:ANESTH. IRRIT OF RESP TRACT OR ACUTE NERV
SYSTEM HDCH, DIZZ, STAGGER, CONFUSN, UNCON OR COMA

=====
===== First Aid Measures =====

First Aid:INHAL: REMOVE FROM FUMES, RESTORE BREATH, KEEP WARM & QUIET,
CALL MD. EYES: PRIMARY IRRIT, FLUSH W/WATER FOR 15 MINS. TAKE TO MD

FOR DEFINITE MEDICAL TREATMENT. SKIN: REMOVE W/SOAP & WATER. REMOVE
CON TAMINATED CLOTHES.

=====
===== Fire Fighting Measures =====

Flash Point:70F;21C, TCC

Extinguishing Media:NFPA CLASS B EXTINGUISHERS (CO*2, DRY CHEM, OR
FOAM).

Fire Fighting Procedures:LIQ. FIRES- WATER SPRAY POSS INEFFECT. COOL
CLSD CANS W/H*2O

Unusual Fire/Explosion Hazard:(SEE OTHER PRECAUTIONS). KEEP HEAT FROM
CONTAINERS TO PREVENT PRESS BUILDUP & POSS AUTOIGNITION.

=====

=====
===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION (FLAMES, HOT
SURFACES, & ELECTRICAL, STATIC OR FRICTIONAL SPARKS). AVOID
BREATHING VAPORS. VENTILATE AREA. REMOVE W/INERT ABSORBNT & NON
SPARKING TOOLS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT HIGH TEMPS. KEEP AWAY
FROM OPEN FLAME & SPARKS. GROUND CONTAINERS WHEN POURING.

Other Precaut

ions:IN FIRE- KEEP CONTAINERS TIGHTLY CLOSED. ISOLATE FROM HEAT, ELECTRICAL EQUIPMNT, SPARKS & OPEN FLAME. CLOSED CONTAINER MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT TAKE CMPD INTERNALLY.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED CHEM-MECHANICAL FILTER RESPIRATOR.

Ventilation:LOCAL TO MAINTAIN BELOW TLV.

Protective Gloves:REQUIRED

Eye Protection:SPLASH-PROOF GOGGLES.

Other Protective Equipment:PROTECTIVE CLOTHING-WASH FREQUENTLY, SO AS NOT TO HARM SKIN

Supplemental Safety and Health CONTAINER SIZE=1 GALLON.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:275F;135C

Vapor Pres:0.5

Vapor Density:3.6

Spec Gravity:0.97

Solubility in Water:NEGLIGIBLE

Percent Volatiles by Volume:55

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Hazardous Decomposition Products:EMITS ACRID FUMES & MAY EXPLODE.

===== Disposal Considerations =====

Waste Disposal Methods:DISPOSE OF IAW FED, STATE & LOCAL CODES. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its u

se. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.