

TRIRAM CORP -- PR-50-AF,TT-C-498B, COATING COMPOUND -- 8030-00-664-7042

=====
Product Identification
=====

Product ID:PR-50-AF,TT-C-498B, COATING COMPOUND

MSDS Date:01/01/1985

FSC:8030

NIIN:00-664-7042

MSDS Number: BFKRW

=== Responsible Party ===

Company Name:TRIRAM CORP

Emergency Phone Num:(617) 875-6600

CAGE:59983

=== Contractor Identification ===

Company Name:TRIRAM CORP

Address:721 WAVERLY ST

Box:642

City:FRAMINGHAM

State:MA

ZIP:01701-8512

Country:US

CAGE:59983

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

OSHA PEL:100 PPM

Ingred Name:ALUMINUM PIGMET PERCENT IS APPX

Fraction by Wt: 11%.

=====
Hazards Identification
=====

Effects of Overexposure:MFR STATES SAME AS ANY PETROLEUM DERIVATIVE

=====
First Aid Measures
=====

First Aid:EYE: IMMEDIATELY FLUSH W/WATER AT LEAST 15 MIN. CALL MD.

SKIN: WASH THOROUGHLY AFTER HANDLING

=====
Fire Fighting Measures
=====

Flash Point:124F COC

Extinguishing Media:CO*2, FOAM, SAND

Fire Fighting Procedures:SIMILAR TO OTHER PETROLEUM PRODUCTS

Unusual Fire/Explosion Hazard:NONE-SIMILAR TO OTHER PETROLEUM PRODUCTS

=====
Accidental Release Measures
=====

Spill Release Procedures:DRY W/NORMAL GARAG

E FLOOR CLEANER, I E SPEEDY

OIL DRY. MFR SUGGESTS USING MINERAL SPIRITS OR KEROSENE ON DRIED
MATL TAKING PRECAUTIONS AGAINST FIRE & INH HAZ.

=====
Handling and Storage
=====

Handling and Storage Precautions:AVOID EXCESSIVE HEAT OR MOISTURE

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:NIOSH/MSHA APPRVD RESP PROT IF NEC

Ventilation:LOCAL EXHST, YES

Protective Gloves:IF NEC

Eye Protection:GOGGLES IF NEC

Oth

er Protective Equipment:AS REQ

Supplemental Safety and Health

MFR'S ADDRESS: TRITAM CORP, 721 WAVERY ST, FRAMINGHAM, MA 01701

=====
Physical/Chemical Properties
=====

HCC:F4

NRC/State Lic Num:NA

Boiling Pt:B.P. Text:313F

Spec Gravity:1.04

Evaporation Rate & Reference:0.06

Appearance and Odor:SILVER COLOR, ODOR SIMILAR TO MINERAL SPIRITS

=====
Stability and Reactivity Data
=====

Stability Indicator/Materials to Avoid:YES

WATER

Stabilit

y Condition to Avoid:EXCESSIVE HEAT

Hazardous Decomposition Products:NONE

=====
Disposal Considerations
=====

Waste Disposal Methods:DISPOSE IAW LOCAL, STATE, FED REG

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liabi

lity for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.