View NSN Online: https://aerobasegroup.kr/nsn/6750-00-680-1557

EASTMAN KODAK COMPANY -- 153 6531,PHOTO RSIST THNNR FOR PHOTOENGRAVG - 6750-00-680-1557

Product ID:153 6531, PHOTO RSIST THNNR FOR PHOTOENGRAVG MSDS Date:01/01/1985 FSC:6750 NIIN:00-680-1557 **MSDS Number: BFLGS** === Responsible Party === Company Name: EASTMAN KODAK COMPANY Address:343 STATE STREET City:ROCHESTER State:NY ZIP:14650 Country:US Info Phone Num:716-722-5 151 Emergency Phone Num:716-722-5151 CAGE:19139 === Contractor Identification === Company Name: EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS Address:343 STATE ST Box:City:ROCHESTER State:NY ZIP:14650-1115 Country:US Phone:716-722-5151/(800) 242-2424 CAGE:19139 

Ingred Name:2-METHOXYETHYL ACETATE (EGMEA) CAS:110-49-6 RTECS #:KL5950000 Fraction by Wt: 96.5% OSHA PEL:S, 25 PPM ACGIH TLV:S, 5 PPM; 9192

Ingred Name:NON-AQUEOUS SOL

UTION, HAZARD UNKNOWN, UNIDENTIFIED (2-5%)	
Fraction by Wt: 3.5%	

======================================
Effects of Overexposure:EYES:LIQ CONTCT MAY IRRITATE;SKIN:PROLNGD/REPEATD CONTCT MAY CAUSE IRRIT.MAY BE *SEE SUPPL DATA*
======================================
First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.FOR BURNS GET MED ATTN.
======================================
Flash Point:120F(49C)-TCC Lower Limits:1.7 Upper Limits:8.2
Extinguishing Media:CO*2,DRY CHEM, DRY FOAM Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.
Unusual Fire/Explosion Hazard:RUNOFF/SPILL MAY CAUSE POLLUTION/FIRE HAZARD.
======================================
Spill Release Procedures:ELIM IGN SOURCE S.EVACUATE UNPROTECTED PERSONS.MFR STATE:HAVE GOOD VENTILATION-USE RESPIRATOR.CLEAN W/ABSORPTIVE-SAWDUST,RAGS,ETC.FLUSH WELL W/H*20.STATE/LOCAL LAWS TAKE PRECEDENCE;LG SPILL:DIKE LIQ & PUMP TO SALVAGE TANK PENDING DISPOSAL
======================================

Handling and Storage Precautions:STORE AWAY FROM STRONG ALKALI.STORE IN COOL,DRY PLACE.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICALDAMAGE. Other Precautions:AVOID SKIN/E

## YE CONTACT W/CHEMICAL P PRODUCTS.WASH THOROUGHLY AFTER HANDLING.

Respiratory Protection: AN APPRVD ORGANIC VAP RESPIRATOR FOR EMERGENCY USE ONLY.

Ventilation:LOCAL EXHAUST & MECHANICAL(GENERAL) RECOMMENDED BY MFGR. Protective Gloves:IMPERVIOUS

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment: AS NECESSARY TO PREVENT SKIN CONTACT.

Supplemental Safety and Health

OVEREXPOSURE EFFECTS: ABSORBED THROUGH THE INT

ACT

SKIN;INH:REPEATD/PROLNGD EXPOSURE TO HIGH CONC MAY RESULT IN CHANGES IN THE BLOOD PICTURE & POSSIBLE KIDNEY DAMAGE;MSDS FM MFR DTD:11-14-77.

HCC:F4 Boiling Pt:B.P. Text:282-291F Vapor Pres:3.3 Vapor Density:4.1 Spec Gravity:1.005 Solubility in Water:COMPLETE Appearance and Odor:COLORLESS LIQUID-AROMATIC ODOR Percent Volatiles by Volume:98%

S

tability Indicator/Materials to Avoid:YES NONE PER MFR. Stability Condition to Avoid:SOURCE OF IGNITION Hazardous Decomposition Products:BURNING MAY RESULT IN THE EVOLUTION OF CO & CO\*2.

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.COMPLY W/ALL APPLICABLE FED,STATE/LOCAL REGS REGARDING DISPOSAL;MFR SUGGESTS CONTROLLED BURNING METHOD OF DISPOSAL IAW FEDERAL,STATE & LOCAL EFFLUENT LAWS C ONC

## ERNING DISPOSAL PROCEDURES/METHODS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.