

EASTMAN KODAK COMPANY -- 194 7738,STOP BATH,PROCESS C-22 -- 6750-00-680-7877

=====
Product Identification
=====

Product ID:194 7738,STOP BATH,PROCESS C-22

MSDS Date:01/01/1985

FSC:6750

NIIN:00-680-7877

Kit Part:Y

MSDS Number: BFLHR

=== Responsible Party ===

Company Name:EASTMAN KODAK COMPANY

Address:343 STATE STREET

City:ROCHESTER

State:NY

ZIP:14650

Country:US

Info Phone Num:716-722-5151

Emergency

Phone Num:716-722-5151

CAGE:19139

=== Contractor Identification ===

Company Name:EASTMAN KODAK CO GOVERNMENT MARKETS CONTRACTS

Address:343 STATE ST

Box:City:ROCHESTER

State:NY

ZIP:14650-1115

Country:US

Phone:716-722-5151/(800) 242-2424

CAGE:19139

=====
Composition/Information on Ingredients
=====

Ingred Name:ACETIC ACID (SARA III)

CAS:64-19-7

RTECS #:AF1225000

Fraction by Wt: 72.5%

OSHA PEL:10 PPM

ACGIH TLV:10 PPM/15 STEL; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

Ing

red Name:AQUEOUS SOLUTION,HAZARD UNKNOWN,UNIDENTIFIED(25-30%)
Fraction by Wt: 27.5%

=====
Hazards Identification
=====

Effects of Overexposure:SKIN/EYES:DIRECT CONTACT W/LIQUID CAUSES IRRITATION.VAPOR IRRITATING.

=====
First Aid Measures
=====

First Aid:INH:REMOVE FROM EXPOSURE.GIVE CPR/OXY IF NEEDED & GET MED ATTN;EYES:FLUSH IMMED W/WATER FOR AT LEAST 15 MIN.GET MED HELP;SKIN:FLUSH IMMED W/PLENTY OF WATER FOR 15 MIN.GET MED ATTN IF IRRITATION DEVELOPS.

=====
Fire Fighting Measures
=====

Flash Point:NONE
Extinguishing Media:CO*2,DRY CHEM
Fire Fighting Procedures:USE SELF-CONTND BRTHG APP;COOL EXPSD CONT W/WATER SPRAY.
Unusual Fire/Explosion Hazard:SPILL/RUNOFF MAY CAUSE POLLUTION,FIRE OR EXPLOSION HAZARD.

=====
Accidental Release Measures
=====

Spill Release Procedures:EVACUATE UNPROTECTED PERSONS.ELIM IGN SOURCES.USE PROTECTV CLOTHNG/SAFETY GLASSES.STOP LEAK W/O RISK.PROVIDE VENT.DIKE LG SPILL & PUMP INTO COVRD DRUMS;ABSORB/CONTAIN SM SPILL IN CONT;MFGR RECOMMENDS, FLUSH TO SEWER W/LG AMT OF WATER IAW EXISTING LAWS

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN COOL,DRY,WELL VENTILATED AREA.KEEP CONTNRS TIGHTLY CLOSED.PROTECT CONTNRS FROM PHYSICAL DAMAGE.
Other Precautions:AVOID PROLONGED/REPEATED CONTACT W/PRODUCT.REMOVE &

WASH CONTAMINATED CLOTHING.WASH HANDS AFTER USE.APPROX PH OF
PRODUCT:3.5

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQD IN NORMAL CONDITIONS.

Ventilation:MECHANICAL(GEN) RECOMMENDED BY MFR & LOCAL EXH IF
NECESSARY.

Protective Gloves:IMPERVIOUS/RUBR

Eye Protection:SAFETY GLASSES/GOGGLES

Other Protective Equipment:AS NEEDED BY LOCAL AUTHORITIES.

Supplemental Safety and Health

KEY 1: PO1; MSDS FM MFR DTD: 4/28/76; ITEM HAS 5 PARTS

(BLEACH,

DEVELOPER, FIXER, HARDENER A & B, & STOP BATH); THIS IS STOP BATH
IN GLASS BOTTLE; SEE OTHER PNI THIS NSN FOR OTHER PARTS. KEY 1: C1

===== Physical/Chemical Properties =====

HCC:F6

Boiling Pt:B.P. Text:>212F/>100C

Vapor Pres:32

Vapor Density:1.16

Spec Gravity:1.12

Solubility in Water:COMPLETE

Appearance and Odor:CLEAR LIQUID,VINEGAR ODOR.

Percent Volatiles by Volume:96%

===== Stability and Reactivity Data =====

Stability

Indicator/Materials to Avoid:YES

STRONG ALKALIS;FLAMM/OXIDIZING MATL.

Stability Condition to Avoid:UNK

Hazardous Decomposition Products:CO,CO*2 BY THERMAL DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods:KEEP IN COVERED CONTAINERS PENDING DISPOSAL.SHIP
WASTE MATL TO DISPOSAL FACILITY IAW DOT/EPA REGS.HANDLE/DISPOSE IN
FULL COMPLIANCE W/ALL INTNL,FED,STATE/LOCAL REGS;MFGR
RECOMMENDS,FLUSH TO SEWER W/LG AMT OF WATER IAW FED,ST

ATE/LOCAL
EFFLUENT LAWS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.