

EMERY CHEMICALS, DIV NATIONAL DISTILLERS&CHEM CORP -- EMERY 2952 SYNTHETIC TURBINE LUBRICANT -- 9150-00-681-5999

=====  
===== Product Identification =====

Product ID:EMERY 2952 SYNTHETIC TURBINE LUBRICANT

MSDS Date:06/18/1986

FSC:9150

NIIN:00-681-5999

MSDS Number: BFLJG

=== Responsible Party ===

Company Name:EMERY CHEMICALS, DIV NATIONAL DISTILLERS&CHEM CORP

Address:4900 ESTE AVENUE

City:CINCINNATI

Stat

e:OH

ZIP:45232

Country:US

Emergency Phone Num:513-482-2297

CAGE:EO063

=== Contractor Identification ===

Company Name:EMERY CHEM DIV OF NATIONAL DISTILLERS & CHEM CORP

Address:11501 NORTHLAKE DR

Box:429557

City:CINCINNATI

State:OH

ZIP:45249-1619

Country:US

Phone:513-482-2297

CAGE:33358

Company Name:EMERY CHEMICALS, DIV NAT'L DISTILLERS

CAGE:EO063

=====  
===== Composition/Information on Ingredients =====

Ingred Name:PENTAERYTHRITOL ESTERS, TECH

Ingred Name:ADDITIVES

=====

==== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

==== First Aid Measures =====

First Aid:INHAL:RMV TO FRESH AIR. IF NOT BRTHNG GIVE CPR; IF BRTHNG  
DIFF GIVE OXYGEN. EYE:IMMED FLUSH W/PLENTY OF WATER. SKIN:WASH  
W/SOAP & WATER. RMV CONTAM CLTHG & SHOES. INGEST:DO NOT INDUCE  
VOMIT. NOTHG BY MOUTH IF UNCONSC. GET MEDICAL ATTN.

=====

==== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:490F/254C  
Extinguishing Media:WATER SPRAY,DRY CHEMICAL,FOAM,OR CARBON  
DIOXIDE.WATE INEFFECTIVE.USE WATER TO COOL CONTAINERS.ALSO WATER  
SPRAY TO DISPRS  
Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS IN THE  
POSITIVE-PRESSURE MODE WITH A FULL FACEPIECE WHEN THERE IS A  
POSSIBILITY OF EXPOSURE TO SMOKE.  
Unusual Fire/Explosion Hazard:NONE

==== Accidental Release Measures =====

Spill Release Procedures:USE SCBA & FULL BODY PROTECTION. CONTAIN  
SPILL,PUMP OR SCOOP INTO CLOSABLE CONTAINERS.COLLECT RESIDUAL  
SPILLAGE W/BIODEGRADABLE DETERGENT & WATER TO SEWER.

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL DRY AREA  
Other Precautions:NONE GIVEN.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:USE MIST RESPIRATOR AS REQD

Ventilation:GENERAL MECHANICAL  
Protective Gloves:IMPERVIOUS  
Eye Protection:SAFETY GLASSES.  
Other Protective Equipment:NONE GIVEN  
Supplemental Safety and Health  
MSDS DTD 18JUN86

===== Physical/Chemical Properties =====

HCC:V6  
Boiling Pt:B.P. Text:>540F, 282C  
Spec Gravity:0.997  
Solubility in Water:NEGLIGIBLE  
Appearance and Odor:AMBER LIQUID, TYPICAL PETROLEUM ODOR.

===== Stability and Reactivity Data =====

Stability Indicator/Materials to  
Avoid:YES  
OXIDIZERS  
Stability Condition to Avoid:EXTREME HEAT, IGNITION SOURCES.  
Hazardous Decomposition Products:CABON OXIDES

===== Disposal Considerations =====

Waste Disposal Methods:RECLAIM OR INCINERATE IAW ALL LAWS & REGS. DO  
NOT LANDFILL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.