

AMERICAN OIL & SUPPLY CO -- LUBE OIL,ACFT -- 9150-00-681-5999

=====
Product Identification
=====

Product ID:LUBE OIL,ACFT

MSDS Date:01/01/1985

FSC:9150

NIIN:00-681-5999

MSDS Number: BFLJK

=== Responsible Party ===

Company Name:AMERICAN OIL & SUPPLY CO

Emergency Phone Num:201-589-0250

CAGE:DO810

=== Contractor Identification ===

Company Name:AMERICAN OIL & SUPPLY CO

Address:233 WILSON AVE

City:NEW

ARK

State:NJ

ZIP:07105

Country:US

Phone:201-589-0250

CAGE:DO810

Company Name:AMERICAN OIL AND SUPPLY CO

Address:239 WILSON AVE

City:NEWARK

State:NJ

ZIP:07105-3824

Country:US

Phone:201-589-0250

CAGE:92895

=====
Composition/Information on Ingredients
=====

Ingred Name:PENTAERYTHRITOL

CAS:115-77-5

RTECS #:RZ2490000

Fraction by Wt: 95%

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3; 9293

=====
Hazards Identification
=====

Effects of Overexposure:IN

HALATION OF MISTS,OR HIGH CONCENTRATIONS MAY
RESULT IN NON SPECIFIC IRRITATION OF RESPIRATORY TRAC

===== First Aid Measures =====

First Aid:INGESTION:INDUCE VOMITING.EYES: FLUSH WITH WATER FOR 15 MIN.
DO NOT NEUTRALIZE OR USE OINTMENTS.SKIN:FLUSH AREA WITH WATER.
INHALATION:REMOVE TO FRESH AIR. IN ALL CASES -CONSULT PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:490F (COC)
Extinguishing Media:WATER
FOG, DRY CHEMICALS, CARBON DIOXIDE
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:MOP OR PUMP INTO CONTAINERS FOR DISPOSAL.
RESIDUALS CAN BE ABSORBED WITH CLAY-TYPE ABSORBENT.

===== Handling and Storage =====

Handling and Storage Precautions:PROLONGED & REPEATED CONTACT WITH SKIN
SHOULD BE AVOIDED. WASH WITH SOAP & WATER & LAUNDER SOILED CL
OTHING
BEFORE REUSE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NOT NORMAL NEEDED
Ventilation:LOCAL EXHAUST
Protective Gloves:RUBBER/VINYL
Eye Protection:SAFETY GLASSES/GOGGLES
Supplemental Safety and Health

===== Physical/Chemical Properties =====

HCC:V6
Boiling Pt:B.P. Text:450F
Vapor Pres:1
Vapor Density:10
Spec Gravity:0.988
Solubility in Water:NEGLIGIBLE
Appearance and Odor:CLEAR, RED MOBILE LIQUID, MILD ODO

R

Percent Volatiles by Volume:1.0

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

Stability Condition to Avoid:AQUEOUS ALKALI WILL SLOWLY SAPONIFY

Hazardous Decomposition Products:NORMAL FOR ORGANIC MATERIALS

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATION

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elem

ents of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.