

GULF OIL CORPORATION(MFR),PHIPPS PRODUCTS(VENDOR) -- GULF PARAMOUNT  
100(FORMERLY PARAMOUNT 58) -- 9150-00-682-6771

=====  
Product Identification  
=====

Product ID:GULF PARAMOUNT 100(FORMERLY PARAMOUNT 58)

MSDS Date:01/01/1987

FSC:9150

NIIN:00-682-6771

MSDS Number: BFLLP

=== Responsible Party ===

Company Name:GULF OIL CORPORATION(MFR),PHIPPS PRODUCTS(VENDOR)

Emergency Phone Num:713-651-0693

CAGE:HO2

56

=== Contractor Identification ===

Company Name:GULF OIL CO U.S. A DIV OF GULF OIL CORP

Box:1519

City:HOUSTON

State:TX

ZIP:77001

Country:US

CAGE:34252

Company Name:GULF OIL CORPORATION

CAGE:HO256

=====  
Composition/Information on Ingredients  
=====

Ingred Name:PETROLEUM HYDROCARBONS

Fraction by Wt: 100%

ACGIH TLV:5MG/CUM OILMIST

=====  
Hazards Identification  
=====

Effects of Overexposure:MAY CAUSE IRRITATION TO EYES,SKIN & RESPIRATORY  
TR

ACT ON CONTACT.INGESTION CAUSES NAUSEA VOMITING.

=====  
First Aid Measures  
=====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O\*2 IF

NEED;EYES/SKIN:FLUSH W LG AMTS H\*2O FOR 15 MIN;INGEST:RINSE MOUTH;  
GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER  
SYMPTOMS OF OVEREXPOSURE.

=====  
Fire Fighting Measures  
=====

Flash Point:202C/395F P-M

Lower Limits:UNKN

Upper Limits:UNKN

Extinguishing Media:CO\*2,

DRY CHEMICAL,FOAM

Fire Fighting Procedures:USE WATER TO KEEP FIRE-EXPOSED CONTAINERS COOL.

Unusual Fire/Explosion Hazard:SLIGHT,WHEN EXPOSED TO HEAT OR FLAME;CAN REACT WITH OXIDIZING MATERIALS.

===== Accidental Release Measures =====

Spill Release Procedures:STOP FLOW.ELIMINATE ALL SOURCES OF IGNITION.USE PROPER PERSONAL PROTECTION.ABSORB OR SCRAPE UP.RECOVER IT FOR FURTHER DISPOSAL.

===== Handling and Storage =====

=

Handling and Storage Precautions:KEEP CONTAINER TIGHTLY CLOSED.KEEP AWAY FROM HEAT OR OPEN FLAMES.DO NOT STORE OR MIX WITH STRONG OXIDANTS.

Other Precautions:AVOID REPEATED OR PROLONGED SKIN CONTACT OR INHALATION OF VAPORS,MISTS,FUMES

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN