

WITCO CHEM. CORP. GOLDEN BEAR DIVISION. -- GB 60M TYP I -- 9160-00-685-0914

=====
Product Identification
=====

Product ID:GB 60M TYP I

MSDS Date:01/01/1985

FSC:9160

NIIN:00-685-0914

MSDS Number: BFLNW

=== Responsible Party ===

Company Name:WITCO CHEM. CORP. GOLDEN BEAR DIVISION.

Emergency Phone Num:(805)393-7110

CAGE:LO813

=== Contractor Identification ===

Company Name:WITCO CHEM. CORP. GOLDEN BE

AR DIVISION.

CAGE:LO813

Company Name:WITCO CHEMICAL GOLDEN BEAR DIVISION

Address:10100 SANTA MONICA BLVD SUITE 1470

Box:City:LOS ANGELES

State:CA

ZIP:90067

Country:US

Phone:805-393-7110

CAGE:4H312

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 100%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

=====
Hazards Identification
=====

E

Effects of Overexposure:SKIN IRRITATION OR DERMATITIS ON PROLONGED EXPOSURE.INHALATION.-DIZZINESS,HEADACHE OR NAUSEA-HI CONC

=====
First Aid Measures
=====

First Aid:EYES: FLUSH W/LG AMTS WATER AT LEAST 15 MIN, CALL MD IMMED.

SKIN: WIPE OFF EXCESS, WASH W/SOAP & WATER. INH: REMOVE VICTIM FROM CONTAM AREA, ADMINISTER FRESH AIR SUPPLY. IF SWALLOWED, DO NOT INDUCE VO MIT.

=====
Fire Fighting Measures
=====

FI

ash Point:250F/121C

Lower Limits:UNKN

Upper Limits:UNKN

Extinguishing Media:DRY CHEMICAL,CO*2,WATERSPRAY,FOAM.

Fire Fighting Procedures:AVOID USE OF WATER

Unusual Fire/Explosion Hazard:MAY CAUSE DENSE SMOKE,USE SCBA IN THIS SITUATION

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE FROM WATER BY SKIMMING. REMOVE W/ABSORBENT MATL, SUCH AS SAND, CLAY, ETC.

===== Handling and Storage =====

Handling and

Storage Precautions:KEEP CNTNR CLOSED. KEEP AWAY FROM HEAT & OPEN FLAME.

Other Precautions:AVOID PROLONGED/REPEATED CNTCT W/SKIN. WASH SKIN W/SOAP & WATER AFTER CNTCT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE

Ventilation:NONE

Protective Gloves:OIL RESIST

Eye Protection:SPLASH GOGGLES

Other Protective Equipment:NONE

Supplemental Safety and Health

MSDS REVISED 14 DEC,1982.MFR SPECIFIED 500PPM AS OSHA PEL AND 100PPM AS ACGIH TLV.M

EETS ASTM D-3487,TYPE I & NEMA REQUIREMENTS

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:284F/140C

Vapor Pres: