

DIV OF MALLINKRODT-BAKER(FORMALLY J.T. BAKER COMP) -- METHYL ETHYL KETONE --
6810-00-687-8429

===== Product Identification =====

Product ID:METHYL ETHYL KETONE

MSDS Date:12/08/1995

FSC:6810

NIIN:00-687-8429

MSDS Number: BFLTL

=== Responsible Party ===

Company Name:DIV OF MALLINKRODT-BAKER(FORMALLY J.T. BAKER COMP)

Address:222 RED SCHOOL LANE

City:PHILLIPSBURG

State:NJ

ZIP:08865-2219

Country:US

In

fo Phone Num:908-859-2151/FAX 908-859-9318

Emergency Phone Num:800-424-9300(CHEMTREC)/908-859-2151

CAGE:LO824

=== Contractor Identification ===

Company Name:CHEMICAL COMMODITIES AGENCY, INC.

Address:27447 PACIFIC STREET

Box:City:HIGHLAND

State:CA

ZIP:92346-2640

Country:US

Phone:909-864-2310

CAGE:60777

Company Name:DIV OF MALLINKRODT-BAKER(FORMALLY J.T. BAKER COMP)

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865-2219

Country:US

Phone:908-859-2151/FAX 908-859-9318

CAGE:LO824

C

Company Name:MALLINCKRODT BAKER, INC.

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:800-582-2537

CAGE:70829

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====
===== Composition/Information on Ingredients =====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA 313) (CERCLA)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 100%

Other REC Limits:NONE RECOMMENDED

OSHA PEL:200 PPM

ACGIH TLV:200 PPM/300STEL;9596

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====

LD50 LC50 Mixture:ORAL RAT LD50: 2737MG/KG.

Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES

Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO

Health Hazards Acute and Chronic:INHAL:CAUSES IRRIT TO

NOSE/THROAT.CONCEN >TLV CAUSE HEAD,DIZZ,NAU,SHORTNESS OF
BREATH,VOMIT.HIGHER CONCEN CAUS

E CNS DEPRESS,UNCONSC.INGEST:CAUSES

IRRIT TO DIGESTIVE TRACT W/ABD SPASMS,NAU,VOMIT.LG DOS ES MAY CAUSE

NARCOSIS.SKIN:CAUSES IRRITW/DISCOLORATION.EYE:VAP IRRIT.SPLASHES

PRODUCE PAINFUL IRRIT,EYE DMG(SIGN/SYMPT)

Explanation of Carcinogenicity:THIS PRODUCT IS NOT LISTED BY IARC, NTP,
OR OSHA AS A CARCINOGEN.

Effects of Overexposure:HEALTH:CHRONIC:PROL SKIN CONTACT MAY DEFAT SKIN
& PRODUCE DERM. IRRIT NOSE/THROAT/DIGESTIVE TRACT/SKIN/EYE.

DISCOLOR SKIN,DIZZINESS,NAUSEA,SHORT

NESS OF BREATHING,VOMITING,CNS

DEPRESS,UNCONSC,ABDOMINAL SPASMS,NARCOSIS,EYE DMG,DERMATITIS.

Medical Cond Aggravated by Exposure:PERSONS W/PRE-EXISTING SKIN

DISORDERS OR EYE PROBLEMS OR IMPAIRED RESPIRATORY FUNCITON MAY BE MORE SUSCEPTIBLE TO EFFECTS OF SUBSTANCE.

===== First Aid Measures =====

First Aid:SWALLOWED INDUCE VOMIT IMMED AS DIRECTED BY MED PERSON.NEVER GIVE ANYTHING BY MOUTH IF UNCONSC.INHAL REMOVE TO FRESH AIR.NOT BREATHIN

G GIVE ART RESP;DIFFI IN BREATHING GIVE OXY.IN CASE OF CONTACT IMME D FLUSH EYE/SKIN W/PLENTY OF WATER FOR @LEAST 15MINS.IN ALL CASES CALL PHYSICIAN.REMOVE CONTAM CLOTHING.WHEN FLUSHING EYES LIFT UPPER/LOWER EYELIDS OCCASIONALLY.

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:=-6.C, 21.2F

Autoignition Temp:=-516.C, 960.8F

Lower Limits:1.8

Upper Limits:11.5

Extinguishing Media:DRY CHEMICAL,FOAM OR CARBON DIOXIDE.WATER SPRAY MAY BE USED TO KEEP FIRE EXPO CNTNRS COOL.

Fire Fighting Procedures:IN EVENT OF FIRE WEAR FULL PROT CLOTH/NIOSH APPROV SCBA W/FULL FCPIECE OPERATED IN PRESSURE DEMAND/OTHER +PRESSURE MODE.

Unusual Fire/Explosion Hazard:>FLASH PT VAP/AIR MIX EXPLO W/IN FLAMM LIMITS NOTED ABOVE.SENSITIVITY TO STATIC DISCHARGE:YES.HIGHLY FLAMM MUST BE KEPT FRM SPARK/OPN FLAME/HOT SURF/HEAT/(SUPP)

===== Accidental Release Measures =====

Spill Release Procedures:VENTI ARE

A.REMOVE ALL IGN SOURCE.WEAR APPRO

PPE.ISOLATE HAZ AREA.KEEP UNNECESSARY/UNPROT PEOPLE FRM

ENTER.CONTAIN/RECOVER LIQ.USE NON-SAPRK TOOL/EQPMT.COLLECT IN

APPROP CNTNR/ABSORB W/INERT MATL.PLACE IN CHEM WASTE CNTNR.DONT USE COMBUST MATL.(SUPP)

Neutralizing Agent:NONE SPECIFIED BY MANUFACTURER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHT CLSD CNTNR.PROTECT AGAINST PHY DMG.STORE IN COOL DRY WELL VENTI AREA A

WAY FRM AREA

WHERE FIRE HAZ MAY BE ACUTE.PREF:OUTSIDE/DETACH STORG

Other Precautions:SEPARATE FRM OXID MATLS.BOND/GROUND CNTNR FOR TRANSF-AVOIDS STATIC SPARKS.STORAGE/USE AREA SHOULD BE NO SMOKING AREA.SPARK-PROOF TOOLS/EXPLO-PROOF EQPMT SHOULD BE USED IN STORAGE/HNDLG AREA.EMPTY CNTN R HAZ-RETAIN RESIDUE,OBSERVE WARN/PRECAU

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH APPROV.EXPO LIMIT EXCEEDED FULL FCPIECE RESP W/ORG

VAP CARTRIDGE MAY BE WORN UP TO 10X EXPO LIMIT/MAX USE CONC SPEC BY RESP SUPPLIER WHICHEVER IS LESS.EMERG/EXPO LEVELS UNK USE +PRESSURE AIR SUP PL RESP.WARN:AIR PURI RESP DONT(SUPPLE)

Ventilation:LOC &/OR GEN EXHAU RECOMMENDED.LOC EXHAU VENTI GENERALLY PREFER-CONTROL EMISSIONS OF CONTAM @SOURCE,PREVENT DISPERSION.

Protective Gloves:IMPERV PROT GLOVES

Eye Protection:CHEM SAF GOGG &/OR FULL FACE SHIELD

Other Protective Equipment:REFER:ACGIH "INDUST VENTI,MANUAL OF RECOMMEND PRACT"

.USE EXPLO-PROOF EQPMT.IMPERV PROT CLOTH:BOOTS,LAB COAT,APRON,COVERA

Work Hygienic Practices:MAINTAIN EYEWASH FOUNTAIN & QUICK-DRENCH FACILITIES IN WORKAREA.

Supplemental Safety and Health

EXPLO/FIRE:IGN SOURCES.VAP CAN FLOW ALONG SURF TO DISTANT IGN SOURCE;FLASHBK. SPILL:DONT FLUSH TO SEWER.WHATEVER CANT BE SAVE FOR RECOV/RECYCL HNDL AS HAZ WASTE-SEND TO RCRA APPROV WASTE FACIL.REPORT SPILL/RELEASE IN EXCESS QUANT.RQ:5000LB.DISPO:IAW FED/STATE/LOC REQMTS.SARA 313 CHEM.RC

RA:U159. RESP:PROTECT IN OXY-DEF

=====
===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt:B.P. Text:176F,80C

Melt/Freeze Pt:M.P/F.P Text:-123F,-86C

Decomp Temp:Decomp Text:NP

Vapor Pres:100

Vapor Density:2.5

Spec Gravity:0.805

pH:NP

Viscosity:NP

Evaporation Rate & Reference:2.7, ETHER=1

Solubility in Water:29G/100G WATER.

Appearance and Odor:CLEAR, COLORLESS LIQUID, SHARP MINT-LIKE ODOR

Percent Volatiles by Volume:100

Corrosion Rate:NP

=====

Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES

OXIDIZ MATLS, CHLOROFORM, CHLOROSULFONIC

ACID, OLEUM, POTASSIUM-T-BUTOXIDE, H₂O₂, NITRIC ACID. ATTACK MANY
PLAST, RESINS, RUBBER.

Stability Condition to Avoid: HEAT OR FLAME

Hazardous Decomposition Products: CARBON DIOXIDE AND CARBON MONOXIDE MAY
FORM WHEN HEATED TO DECOMPOSITION.

===== Disposal Considerations =====

Waste Disposal Methods: PROCESS/USE/CONTAM OF PROD MAY
CHANGE WASTE

MANGM OPTIONS. STATE/LOC DISPO REGS MAY DIFFER FRM FED. US REGS
REQUIRE REPORT SPILL/RELEASE TO SOIL/H₂O/AIR IN EXCESS OF RQ. COAST
GUARD NAT RESP CNTNR 800-42 4-8802. RQ: 5000 LBS. DISPO CNTNR/UNUSED
CONTENTS(SUP)

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to

be accurate and

disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.