

ESSEX CHEMICAL CORP PRO-SEAL DIV -- PRO-SEAL 890 BASE CLASS A -- 8030-00-723-5343

=====
Product Identification
=====

Product ID:PRO-SEAL 890 BASE CLASS A
MSDS Date:01/01/1987
FSC:8030
NIIN:00-723-5343
Kit Part:Y
MSDS Number: BFMLY
=== Responsible Party ===
Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV
Address:19451 SUSANA RD
City:COMPTON
State:CA
ZIP:90221-5713
Country:US
Info Phone Num:310-537-7
600
Emergency Phone Num:310-537-7600
CAGE:83527
=== Contractor Identification ===
Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV
Address:19451 SUSANA RD
Box:City:COMPTON
State:CA
ZIP:90221-5713
Country:US
Phone:310-537-7600
CAGE:83527

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)
CAS:108-88-3
RTECS #:XS5250000
OSHA PEL:200 PPM/150 STEL
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identific
=====

ation =====

Effects of Overexposure:MAY CAUSE SKIN IRRIT. INH MAY LEAD TO NARCOSIS.

===== First Aid Measures =====

First Aid:WASH THOROUGHLY AFTER HANDLING. FOR INH REMOVE TO FRESH AIR.
IF INGESTED, CONSULT MD IMMED. FLUSH EYES W/WATER COPIOUSLY.

===== Fire Fighting Measures =====

Flash Point:68F CC
Lower Limits:1.3
Upper Limits:6.8
Extinguishing Media:CO*2, FOAM, DRY CHEM
Fire Fighting Procedures:W
ATER NOT REC
Unusual Fire/Explosion Hazard:VOLATILE SLVNT

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP W/SLVNT & RAGS, MFR REC

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CNTNRS BELOW 80F.
AVOID OPEN FLAMES, ELECTRICAL SPARKS WHEN USING.
Other Precautions:RED LABEL MATL

===== Exposure Controls/Personal Protection =====

Respiratory Protection
:USE W/ADEQUATE VENTILATION
Ventilation:MECH, DESIRABLE
Protective Gloves:REC
Eye Protection:REC
Other Protective Equipment:APRON, COVERALLS
Supplemental Safety and Health
BP GIVEN FOR SLVNT. 2 PINT SIZE, 2 HR APPLICATION TIME, & BRUSH
APPLICATION. KEY 1: F3

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:230F
Vapor Pres:37
Vapor Density:3.1
Spec Gravity:1.5
Evaporation Rate & Reference:4.5 ETHYLETHER
Solubility in Water:NIL
Appearance a

nd Odor:WHITE SEMI-SOLID FLUID, SULFIDE ODOR
Percent Volatiles by Volume:15

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
AVOID STRONG OXIDIZING AGENTS
Hazardous Decomposition Products:CO*2, H*2O, SO*2 UPON COMBUSTION

===== Disposal Considerations =====

Waste Disposal Methods:BURN WASTE, MFR REC

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.