

BEL-RAY -- VV-G-632A; PRODUCT #2950,GREASE -- 9150-00-753-4649

=====
Product Identification
=====

Product ID:VV-G-632A; PRODUCT #2950,GREASE

MSDS Date:01/01/1987

FSC:9150

NIIN:00-753-4649

MSDS Number: BFNBH

=== Responsible Party ===

Company Name:BEL-RAY

Emergency Phone Num:(201)938-2421

CAGE:FO364

=== Contractor Identification ===

Company Name:BEL-RAY

Box:526

City:FARMINGDALE

State:NJ

ZIP:07727

P

hone:(732) 938-2421

CAGE:FO364

Company Name:BEL-RAY CO, INC. (REPLACED BY CAGE 12474)

Address:111 BOWMAN AVE

Box:526

City:FARMINGDALE

State:NJ

ZIP:07727

Country:US

Phone:908-938-2421

CAGE:4W448

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-95-1

RTECS #:PY8030000

Fraction by Wt: 87.0%

OSHA PEL:5 MG/M3

ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:UNIDENTIFIED COMPONENTS

ACGIH TLV:NOT SPECIFIED

=====

==== Hazards Identification =====

Effects of Overexposure:PROLONGED AND REPEATED SKIN OR EYES CONTACT MAY CAUSE MILD IRRITATION;DO NOT BREATHE OIL VAPORS/MIST

==== First Aid Measures =====

First Aid:INHALE:REMOVE TO FRESH AIR, GIVE CPR/O*2 IF NEED;EYES/SKIN:FLUSH W LG AMTS H*2O FOR 15 MIN;INGEST:RINSE MOUTH; GET MEDICAL ATTENTION FOR EYES, BREATHING DIFFICULTY, OR OTHER SYMPTOMS OF OVEREXPOSURE.

=====

== Fire Fighting Measures =====

Flash Point:350F/177C (C.O.C

Lower Limits:1.0

Upper Limits:6.0

Extinguishing Media:WATER SPRAY,FOG,FOAM,CO*2,DRY CHEMICAL.

Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA WITH FULL PROTECTION.

Unusual Fire/Explosion Hazard:NONE NOTED BY THE MFR.

==== Accidental Release Measures =====

Spill Release Procedures:USE PROPER PERSONAL PROTECTION;USE SUITABLE OIL ABSORBENT MATERIAL;RECOVER FOR PROPER DISPOSAL

==== Handling and Storage =====

Handling and Storage Precautions:STORE IN CLOSED CONTAINERS AWAY FROM HEAT AND OPEN FLAMES.

Other Precautions:AVOID CONTACT WITH SKIN AND EYES.DO NOT BREATHE VAPORS/MIST. WASH THOROUGHLY AFTER EACH USE.

==== Exposure Controls/Personal Protection =====

Respiratory Protection:NO SPECIAL REQMENTS UNDER ORDINARY CONDITIONS/ADEQUATE VENT.

Ventilation:PROVIDE MECHAN(GEN/LOCAL EXHAUST)VENT TO MAINTN

600F/316C

Vapor Pres:10

Spec Gravity:0.89

Solubility in Water:NEGLIGIBLE

Appearance and Odor:TAN GREASE,OIL ODOR

Percent Volatiles by Volume: