

NONFLUID OIL CORP -- VV-G-632A GENERAL PURPOSE GREASE -- 9150-00-753-4649

=====  
Product Identification  
=====

Product ID:VV-G-632A GENERAL PURPOSE GREASE

MSDS Date:01/01/1989

FSC:9150

NIIN:00-753-4649

MSDS Number: BFNBL

=== Responsible Party ===

Company Name:NONFLUID OIL CORP

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Info Phone Num:201-344-3451

Emergency Phone Num:201-3

44-3451

CAGE:76736

=== Contractor Identification ===

Company Name:NONFLUID OIL CORP/NFO TECHNOLOGIES, INC

Address:298 DELANCY ST

City:NEWARK

State:NJ

ZIP:07105-3009

Country:US

Phone:201-344-3451/800-424-9300(CHEMTREC)

CAGE:76736

=====  
Composition/Information on Ingredients  
=====

Ingred Name:HYDROTREATED HEAVY NAPHTHENIC DISTILLATE, PETROLEUM

CAS:64742-52-5

RTECS #:PY8035000

Fraction by Wt: 100%

Other REC Limits:NONE SPECIFIED

OSHA PEL:5 MG/M3 (OIL MIST)

ACGIH TLV:5 MG/M3 (OIL

MIST)

=====  
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:YES Ingestion:NO  
Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO  
Health Hazards Acute and Chronic:HEALTH HAZARDS: ACUTE: PROLONGED OR  
REPEATED SKIN CONTACT TENDS TO REMOVE SKIN OILS AND MAY CAUSE SKIN  
IRRITATION. CHRONIC: NONE SPECIFIED BY MANUFACTURER.

=====  
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH PLENTY OF WATER.SEE  
DOCTOR. SKIN: WIPE OFF  
AND WASH WITH SOAP AND WATER. INHALATION: REMOVE TO FRESH AIR.  
INGESTION: GIVE WATER.DO NOT INDUCE VOMITING.SEE DOCTOR. --IF  
PRODUCT IS INJECTED UNDER THE SKIN,SEE DOCTOR IMMEDIATELY  
REGARDLESS OF APPEARANCE OR SIZE.THIS IS A SERIOUS MEDICAL  
EMERGENCY--

=====  
===== Fire Fighting Measures =====

Flash Point Method:COC  
Flash Point:390F,199C  
Lower Limits:1  
Upper Limits:6  
Extinguishing Media:USE WATER FOG, CARBON DIOXIDE, FOAM  
, OR DRY  
CHEMICAL. (USE WATER FOG CAREFULLY TO PREVENT FROTHING).  
Fire Fighting Procedures:WEAR FIRE FIGHTING PROTECTIVE EQUIPMENT AND A  
FULL FACED SELF CONTAINED BREATHING APPARATUS. COOL FIRE EXPOSED  
CONTAINERS WITH WATER SPRAY.  
Unusual Fire/Explosion Hazard:COMBUSTION OR HEAT OF FIRE MAY PRODUCE  
HAZARDOUS DECOMPOSITION PRODUCTS AND VAPORS.

=====  
===== Accidental Release Measures =====

Spill Release Procedures:SCRAPE UP GREASE. WASH REMAINDER WITH SUITABLE  
PETROLEUM SOLVENT. ABSORB IN INERT MATERIAL AND PLACE IN APPROPRIATE  
DISPOSAL CONTAINER AND COVER. WASH AREA WITH SOAP AND WATER.

=====  
===== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY, WELL VENTILATED,  
LOW FIRE RISK AREA. PROTECT FROM HEAT, OPEN FLAMES AND OXIDIZING  
MATERIALS. KEEP CONTAINERS CLOSED.  
Other Precautions:AVOID REPEATED CONTACT WITH SKIN. AVOID CONTACT WITH  
EYES AND INHALATION OF FUMES, VAPORS,

OR MISTS. DO NOT INGEST. WASH  
THOROUGHLY AFTER HANDLING.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE NORMALLY NEEDED. RECOMMENDED RESPIRATORY  
PROTECTION IF FUMING OR MISTING.

Ventilation:NO SPECIAL REQUIREMENT. MECHANICAL (GENERAL) AND/OR LOCAL  
EXHAUST VENTILATION RECOMMENDED IF FUMING OR MISTING.

Protective Gloves:NITRILE,PVA FOR PROLONGED CONTACT.

Eye Protection:SAFETY GLASSES.

Other Protective Equipment:OIL RESISTANT APRON.

Work

Hygienic Practices:WASH THOROUGHLY AFTER HANDLING.LAUNDER  
CONTAMINATED CLOTHING BEFORE REUSE.

Supplemental Safety and Health

NONE.

===== Physical/Chemical Properties =====

HCC:V6

Boiling Pt:B.P. Text:600F,316C

Vapor Pres:10

Spec Gravity:0.9

Evaporation Rate & Reference: