

SEAGRAVE COATING CORP CHEMRAY DIVISION -- F-120, MIL-P-15930, VINYL CHROMATE PRIMER  
-- 8010-00-753-4714

===== Product Identification =====

Product ID:F-120, MIL-P-15930, VINYL CHROMATE PRIMER  
MSDS Date:01/01/1987  
FSC:8010  
NIIN:00-753-4714  
MSDS Number: BFNCC  
=== Responsible Party ===  
Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION  
Address:209 N MICHIGAN AVE  
City:KENILWORTH  
State:NJ  
ZIP:07033  
C  
Country:US  
Info Phone Num:201-245-1111  
Emergency Phone Num:201-245-1111  
CAGE:8D124  
=== Contractor Identification ===  
Company Name:SEAGRAVE COATING CORP CHEMRAY DIVISION  
Address:209 N MICHIGAN AVE  
Box:City:KENILWORTH  
State:NJ  
ZIP:07033  
Country:US  
Phone:201-245-1111  
CAGE:8D124

===== Composition/Information on Ingredients =====

Ingred Name:METHYL ISOBUTYL KETONE (SARA III)  
CAS:108-10-1  
RTECS #:SA9275000  
Fraction by Wt: 32.5%  
OSHA PEL:100 PPM/75 STEL  
ACGIH TLV:50 PPM/75 STEL; 929

3

EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 32.5%  
OSHA PEL:200 PPM/150 STEL  
ACGIH TLV:50 PPM; 9293  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

Ingred Name:TRIORTHOCRESYL PHOSPHATE  
CAS:78-30-8  
RTECS #:TD0350000  
Fraction by Wt: 10%  
OSHA PEL:S, 0.1 MG/M3  
ACGIH TLV:S, 0.1 MG/M3; 9192

Ingred Name:VINYL CHLORIDE VINYL ACETATE COPOLYMER W/TRICRESYL  
PHOSPHATE, 20% OF PROD  
Fraction by Wt: 10%

Ingred Name:ZINC CHROMATE  
CA  
S:13530-65-9  
RTECS #:GB3290000  
Fraction by Wt: 15%  
OSHA PEL:0.1 MG/M3 (CRO3)  
ACGIH TLV:0.01MG/M3(CR)A1;9192

===== Hazards Identification =====

Effects of Overexposure:MAY IRRIT SKIN/RESP SYS. OVER INH MAY CAUSE  
LOWERING OF BODY TEMP/HEART/RESP RATE.

===== First Aid Measures =====

First Aid:FLUSH EXPOSED SKIN FREELY W/WATER. CALL MD IF NEC. IF OVER  
INH OCCURS REMOVE TO WELL-VENT AREA.

===== Fire

Fighting Measures =====

Flash Point:45F TOC

Lower Limits:1.2

Upper Limits:7.5

Extinguishing Media:DRY CHEM, CO\*2

Fire Fighting Procedures:WATER SPRAY MAY BE INEFF AS EXTINGUISHING AGENT

Unusual Fire/Explosion Hazard:VAPORS CAN TRAVEL GREAT DISTANCE & FLASH BACK TO ORIGIN

===== Accidental Release Measures =====

Spill Release Procedures:FOLLOW GENERAL CLEANING PROCEDURES. SM SPILLS MAY BE WASHED AWAY W/WATER, MFR REC.

=====

=== Handling and Storage =====

Handling and Storage Precautions:STORE IN COOL, DRY PLACE AWAY FROM OPEN FLAMES/PHYSICAL ABUSE & W/GOOD VENT.

Other Precautions:ODOR THRESHOLD NOT SUFFICIENT TO WARN OF DANGEROUS CONC. SECURE ALL SOURCES OF IGNIT. KEEP CNTNRS CLOSED AS MUCH AS POSS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CNTND BRTNG APPARATUS, NIOSH/MSHA APPRVD

Ventilation:USE LOCAL & MECH EXHST

Protective Gl

oves:YES

Eye Protection:YES

Supplemental Safety and Health

LMPBLCK, MG-SIO\*4 & ZN-CRO\*4 FORM 15%.AL STERATE