

GENERAL ADHESIVES -- NEOPRENE ADHESIVE 77 X X 1515 -- 8040-00-754-2685

===== Product Identification =====

Product ID:NEOPRENE ADHESIVE 77 X X 1515

MSDS Date:11/11/1985

FSC:8040

NIIN:00-754-2685

MSDS Number: BFNND

=== Responsible Party ===

Company Name:GENERAL ADHESIVES

Address:6100 CENTENNIAL BLVD.

City:NASHVILLE

State:TN

ZIP:37209

Info Phone Num:(615) 367-7833

Emergency Phone Num:(615) 367-7833

Preparer's Name:HENRY PILLOW

CAGE:OFXY2

=== Contractor Identification ===

Company Name:GENERAL ABRASIVE CO DIV OF DRESSER INDUSTRIES INC

Address:2000 COLLEGE AVE

Box:City:NIAGARA FALLS

State:NY

ZIP:14305-1734

Country:US

Phone:716-286-1234

CAGE:84330

Company Name:GENERAL ADHESIVES AND CHEMICAL COMPANY

CAGE:OFXY2

===== Composition/Information on Ingredients =====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA

Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:N-HEPTANE
CAS:142-82-5
RTECS #:MI7700000
OSHA PEL:500 PPM/500 STEL
ACGIH TLV:400 PPM/500STEL;9293

=====
===== Hazards Identification =====

Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES
Reports of Carcinogenicity:NTP:NO
IARC:NO OSHA:NO

Health Hazards Acute and Chronic:IF THIS PRODUCT IS SWALLOWED VICTIM
MAY EXPERIENCE DIZZINESS, NAUSEA, GASTROINTESTINAL IRRITATION,
VOMITING & DIARRHEA. REPEATED OR PROLONGED EXPOSURE MAY CAUSE
DRYING, FISSURING & DERMATITIS.

Explanation of Carcinogenicity:NONE

Effects of Overexposure:ASPIRATION OF MATERIAL INTO THE LUNGS DUE TO
VOMITING CAN CAUSE CHEMICAL PNEUMONITIS WHICH CAN BE FATAL.

Medical Cond Aggravated by Exposure:PRE-EXISTING CENTRAL & PERIPHERAL
NERVOUS SYSTEM, PRE-EXISTING EYE & SKIN DISORDERS.

=====
===== First Aid Measures =====

First Aid:EYES: FLUSH WITH LARGE AMTS OF WATER, LIFTING THE LOWER &
UPPER LIDS OCCASIONALLY. IF IRRITATION PERSISTS AFTER WASHING, GET
MED ATT. CONTACT LENSES SHOULDN'T BE WORN WHEN WORKING W/THIS
PRODUCT. INHA LATION: MOVE EXPOSED TO FRESH AIR AT ONCE. IF
BREATHING HAS STOPPED, PERFORM ARTIFICIAL RESPIRATION. KEEP THE
AFFECTED PERSON WARM & REST. GET MEDI

CAL ATTENTION AS SOON AS
POSSIBLE.

===== Fire Fighting Measures =====

Flash Point Method:TCC

Flash Point:25F

Lower Limits:1.2%

Upper Limits:10.0%

Extinguishing Media:CO2, DRY CHEMICAL, FOAM, HALON

Fire Fighting Procedures:WEAR SELF-CONTAINED BREATHING APPARATUS (SCBA)
AND FULL PROTECTIVE CLOTHING.

Unusual Fire/Explosion Hazard:HEAT MAY CAUSE PRESSURE BUILDUP,
EXPLOSION OF CONTAINERS. WATER COOL CONTAINERS.

===== Accidental Release Me
asures =====

Spill Release Procedures:REMOVE/ELIMINATE ALL SOURCES OF IGNITION.
VENTILATE AREA OF SPILL OR LEAK. FOR SMALL QUANTITIES ABSORB ON
PAPER TOWELS. LARGE QUANTITIES SHOULD BE RETAINED BY DIKING &
ABSORBED WITH ABSORBENT MATERIAL

===== Handling and Storage =====

Handling and Storage Precautions:KEEP PRODUCT CONTAINERS COOL, DRY &
AWAY FROM SOURCES OF IGNITION. USE & STORE THIS PRODUCT WITH
ADEQUATE VENTILATION.

Othe

r Precautions:THIS PRODUCT SHOULDN'T BE ALLOWED TO ENTER A CONFINED
SPACE, SUCH AS A SEWER, BECAUSE OF THE POSSIBILITY OF VAPOR
BUILD-UP, POSSIBLY ALLOWING AN EXPLOSION. PERSONS SHOULD AVOID
BREATHING VAPORS.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:IF TLV EXCEED, USE NIOSH/MSHA APPROVED
RESPIRATOR TO PREVENT OVEREXPOSURE. USE EITHER A AIR SUPPLIED
RESPIRATOR OR ORGANIC VAPOR RESPIRATOR.

Ventilation:PROVIDE LOCAL EXHAUST VEN

TILATION TO KEEP