

MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION -- ETHYL ACETATE AR -- 6810-00-754-2817
===== Product Identification =====

Product ID:ETHYL ACETATE AR

MSDS Date:01/01/1987

FSC:6810

NIIN:00-754-2817

MSDS Number: BFNNQ

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION

Address:PARIS BYPASS

Box:M

City:PARIS

State:KY

ZIP:40361

Country:US

Info Phone Num:314-982-5000

Emergenc

y Phone Num:314-982-5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SPECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

===== Composition/Information on Ingredients =====

Ingred Name:ETHYL ACETATE (SARA III)

CAS:141-78-6

RTECS #:AH5425000

Fraction by Wt: >99%

OSHA PEL:400 PPM

ACGIH TLV:400 PPM; 9192

EPA Rpt Qty:5000 LBS

DOT Rpt Qty:5000 LBS

===== Haz

ards Identification =====

Effects of Overexposure:INH:IRRITNT TO NOSE/RESP TRCT;ING:CAUSES
DIARRHEA,SORE THROAT;SKIN:DEFATS,IRRIT,EYES:IRRITATION.

===== First Aid Measures =====

First Aid:INHAL:REMOVE TO FRESH AIR. GIVE CPR/OXYGEN IF
NEEDED;INGEST:IF SWALLOWED,GIVE TWO GLASSES OF WATER & INDUCE
VOMIT.NOTHING BY MOUTH IF UNCON;SKIN/EYE EXPOSURE;RMV CONTMNTD
CLOTHG.WASH SKIN W/SOAP & H*2 O.FLUSH SKIN/EYES W/LG H*2O;GET MED

HELPIMMEDIATL

===== Fire Fighting Measures =====

Flash Point Method:CC

Flash Point:=-4.4C, 24.F

-4.4C(24F)-C.C.

Autoignition Temp:Autoignition Temp Text:427C

Lower Limits:2.2

Upper Limits:11.0

Extinguishing Media:DRY CHEMICALS,FOAM,CO*2;WATER SPRAY TO KEEP EXPD
CANS COOL

Fire Fighting Procedures:USE H*20 TO COOL EXPD CONTRS. USE SCBA & FULL
PROT.CLTHG.

Unusual Fire/Explosion Hazard:ABOVE FLASH POINT,VAP-AIR MIXTURES ARE
EXPLOSIVE WITHIN FLAMMAB
LE LIMIT; AUTO IGN TEMP:427C(800F)

===== Accidental Release Measures =====

Spill Release Procedures:RMV IGN SOURCES.VENT AREA.UE RESP PROTCTION &
PROTCTV CLOTHG.KEEP OUT OF SURF H*2O,SEWRS/CONFND AREAS;SM
SPILL:ABSORB W/PAPER TOWELS.EVAP UNDER FUME HOOD THEN BURN
CAREFULLY;LG SPILL:DIKE AREA.CONTAIN & RECOVER SPILL IF POSS;SHOVL
RESIDUE INTO DRUMS.

===== Handling and Storage =====

Handling and Storage Precautions

:PROTECT AGAINST PHYSICAL DAMAGE. STORE
IN COOL, DRY WELL VENTILATED AREA AWAY FROM HEAT SOURCES, OXIDIZING
MATERIALS. OUTSIDE OR DETACHED STORAGE IS PREFERRED.
Other Precautions: KEEP AWAY FROM HEAT, SPARKS, FLAMES. KEEP CONTAINERS
CLOSED. USE WITH ADEQUATE VENTILATION. AVOID BREATHING DUST. WASH THOROUGHLY AFTER
HANDLING. BOND/GROUND CONTAINERS WHEN TRANSFERRING MATERIAL. USE NON-SPARKING TYPE
TOOL & EQUIP.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection: FULL FACE RESPIRATOR
Ventilation:
n: LOCAL EXHAUST TO MAINTAIN BELOW TLV.
Protective Gloves: IMPERMEABLE
Eye Protection: GOGGLES/FACE SHIELD
Other Protective Equipment: FULL PROTECTIVE CLOTHING, SAFETY SHOWER, EYE
WASH STATION
Supplemental Safety and Health
MSDS FROM MANUFACTURER DATED: 22 AUG 85, CONFORMS TO OSHA HAZ COMM STD.

=====
===== Physical/Chemical Properties =====

HCC: F2
Boiling Point: B.P. Text: 77°C (171°F)
Vapor Pressure: 76
Vapor Density: 3.0
Specific Gravity: 0.9
Evaporation Rate & Reference: 6 (BUT ACETATE=1)
Solubility in
Water: MODERATE
Appearance and Odor: COLORLESS LIQUID. PLEASANT FRUITY ODOR.
Percent Volatiles by Volume: 100

=====
===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
STRONG OXIDIZERS, STRONG ALKALIES/ACIDS. NITRATES.
Stability Condition to Avoid: HEAT, IGNITION SOURCES
Hazardous Decomposition Products: CO, CO₂ WHEN HEATED TO DECOMPOSITION
Conditions to Avoid Polymerization: HEAT WILL CONTRIBUTE TO
INSTABILITY. SLOWLY DECOMPOSED BY MOISTURE

=====

===== Disposal Considerations =====

Waste Disposal Methods: LG SPILL & LOT SIZES OF HAZ WASTE CAN BE ATOMIZED IN A RCRA APPRVD COMBUSTION CHAMBER OR DISPOSED OF IN A RCRA APPROVED LAND FILL FACILITY. DO NOT FLUSH TO SEWER. ENSURE COMPLIANCE W/ FED, STATE, & LOCAL REGS; REPORTABLE QTY (RQ) (CWA/CERCLA): 5000 LBS

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense

. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.