View NSN Online: https://aerobasegroup.kr/nsn/5970-00-755-9003

STERLING GROUP (NU-BRITE CHEMICAL CO INC) -- STERLING THERMOPOXY

U-122;PRO.CODE:80-122 -- 5970-00-755-9003

============= Product Identification ==============

Product ID:STERLING THERMOPOXY U-122;PRO.CODE:80-122

MSDS Date:03/11/1988

FSC:5970

NIIN:00-755-9003

MSDS Number: BFNPN === Responsible Party ===

Company Name: STERLING GROUP (NU-BRITE CHEMICAL CO INC)

Address:NINE OHIO RIVER BLVD

City:SEWICKLEY

State:PA ZIP:1

5143-2199 Country:US

Info Phone Num:412-766-7600

Emergency Phone Num:412-766-7600

Preparer's Name: MARK DUBOIS

CAGE:LO908

=== Contractor Identification ===

Company Name: NU-BRITE CHEMICAL CO INC, STERLING GROUP

Address:NINE OHIO RIVER BLVD

Box:City:SEWICKLEY

State:PA

ZIP:15143-2199 Country:US

Phone: CHEMTREC 800-424-9300

CAGE:78580

Company Name: STERLING GROUP (NU-BRITE CHEMICAL CO INC)

Address:NINE OHIO RIVER BLVD

City:SEWICKLEY

State:PA

ZIP:15143-2199 Country:US

Phone:412-766-7600

CAGE:LO908

====

| ====== Composition/Information on Ingredients ======== |
|--|
| Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 20-30% OSHA PEL:100 PPM/150 STEL ACGIH TLV:100 PPM/150STEL;9192 EPA Rpt Qty:1000 LBS DOT Rpt Qty:1000 LBS |
| Ingred Name:OTHER COMPONENTS(NOT SPECIFIED) Fraction by Wt: BALANCE |
| ========== Hazards Identification =========== |
| Routes of Entry: Inhalation:YES Skin:YES Ingestion:YES Health Hazards Acute and Chronic: ACUTE:IRRITATION OF EYES,SKIN,RESPIRATORY OR G.I. TRACTS;MAY CAUSE REDNESS,TEARING & BLURRED VISION;HEADACHE,DIZZINESS,INCOORDINATION,NAUSEA,LOSS OF CONSCIOUSNESS,ANESTHETIC. CHRONIC:DERMATITIS,LUNG DAMAGE,CNS EFFECTS,DEFATTING OF SKIN.(BRAIN DAMAGE POSSIBLE.) Effects of Overexposure:SEE HEALTH HAZARDS DATA. Medical Cond Aggravated by Exposure:PRE-EXISTING CONDITIONS MAY BE WORSEN(RESPIRATORY DISORDERS). |
| ====================================== |
| First Aid:INHALATION:REMOVE TO FRESH AIR;CONSULT A PHYSICIAN AT ONCE. SKIN & EYES:FLUSH WITH PLENTY OF WATER FOR ABOUT 15 MINUTES;SEEK MEDICAL ATTENTION IMMEDIATELY. INGESTION:DO NOT INDUCE VOMITING,CALL A PHYS ICIAN IMMEDIATELY. |
| ====================================== |
| Flash Point Method:SCC Flash Point:78F/25.6C Lower Limits:1.0 Upper Limits:7.0 Extinguishing Media:FOAM,CO*2,DRY CHEMICAL,WATER FOG Fire Fighting Procedures:USE NIOSH/MSHA APPROVED SCBA I |

| N AN ENCLOSED AREA. |
|--|
| Unusual Fire/Explosion Hazard:AVOID EXTREME HEAT, VAPORS MAY FORM AN EXPLOSIVE MIXTURE IN AIR. |
| ======== Accidental Release Measures ========== |
| Spill Release Procedures:USE PROPER PERSONAL PROTECTION;REMOVE ALL IGNITION SOURCES;USE SUITABLE INERT ABSORBENT MATERIAL AND RECOVER IN A CLOSED CONTAINER. |
| ============= Handling and Storage ============= |
| Handling and Storage Precautions:STORE IN COOL,DRY AND WELL VENTILATED |
| AREA.KEEP AWAY FROM HEAT,OPEN FLAMES OR SPARKS;KEEP CONTAINERS CLOSED WHEN NOT IN USE. |
| ====== Exposure Controls/Personal Protection ======== |
| Respiratory Protection:USE NIOSH/MSHA APPROVED RESPIRATOR FOR ORGANIC VAPORS/MIST IF ABOVE TLV/PEL OR SCBA IN AN ENCLOSED AREA. Ventilation:LOCAL/GENERAL TO MAINTAIN PEL/TLV Protective Gloves:NEOPRENE,RUBBER Eye Protection:FACE SHIELD OR CHEMICAL GOGGLES Other Protective Equipment:APRON,EYE-WASH & SAFETY SHOWER Work Hygienic Practi ces:AVOID CONTACT WITH EYES AND SKIN;DO NOT BREATHE VAPORS/MIST;WASH THOROUGHLY AFTER EACH USE. Supplemental Safety and Health |
| ========= Physical/Chemical Properties ========== |
| HCC:F3 Boiling Pt:=138.3C, 281.F Vapor Pres:21 Vapor Density:>1.0 Spec Gravity:0.9 Evaporation Rate & Description Evaporation E |