

GOODYEAR TIRE & RUBBER CO -- PLIBOND 30 -- 8040-00-764-4424

=====  
Product Identification  
=====

Product ID:PLIBOND 30

MSDS Date:01/01/1987

FSC:8040

NIIN:00-764-4424

MSDS Number: BFNTX

=== Responsible Party ===

Company Name:GOODYEAR TIRE & RUBBER CO

Address:1144 E MARKET ST

City:AKRON

State:OH

ZIP:44316-0001

Country:US

CAGE:DO805

=== Contractor Identification ===

Company Name:GOODYEAR TIRE & RUBBER  
CO

Address:1144 E MARKET ST

Box:City:AKRON

State:OH

ZIP:44316-0001

Country:US

Phone:216-796-1906

CAGE:DO805

Company Name:GOODYEAR TIRE AND RUBBER CO

Address:1144 E MARKET ST

Box:City:AKRON

State:OH

ZIP:44316-0001

Country:US

Phone:330-796-1906/613-996-66669(CANADA)

CAGE:73842

=====  
Composition/Information on Ingredients  
=====

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)

CAS:78-93-3

RTECS #:EL6475000

Fraction by Wt: 60%

OSHA PEL:200 PPM/300 STEL

ACGIH TLV:200

PPM/300STEL 9192  
EPA Rpt Qty:5000 LBS  
DOT Rpt Qty:5000 LBS

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYE,NOSE & THROAT.HEADACHE,NAUSEA  
& NARCOSIS POSSIBLE AT HIGH VAPOR CONCENTRATIONS

===== First Aid Measures =====

First Aid:INHALATION-REMOVE TO FRESH AIR.EYE CONTACT-FLUSH EYES WITH  
PLENTY OF WATER FOR AT LEAST 15 MIN.CALL DOCTOR.SKIN-WASH WITH SOAP  
& WATER.

===== Fire Fighting Measures =====

Flash Point:26F;-3.3C TOC  
Lower Limits:2  
Upper Limits:12  
Extinguishing Media:CO\*2,DRY CHEMICAL;FOAM  
Fire Fighting Procedures:TREAT AS SOLVENT FIRE  
Unusual Fire/Explosion Hazard:NONE

===== Accidental Release Measures =====

Spill Release Procedures:PROVIDE ADEQUATE VENTILATION;TAKE PRECAUTIONS  
AGAINST ALL SOURCES OF IGNITION.SCOOP BULK OF MATERIAL INTO  
CONTAINER FOR DISPOSAL.CLEAN UP WITH RAGS AND SOLVENTS

=  
===== Handling and Storage =====

Handling and Storage Precautions:KEEP AWAY FROM HEAT, SPARKS & OPEN  
FLAME.USE ONLY WITH ADEQUATE VENTILATION.AVOID PROLONGED BREATHING  
OF VAPOR.AVOID SKIN OR EYE CONTACT.

===== Exposure Controls/Personal Protection =====

Eye Protection:SAFETY GLASSES  
Supplemental Safety and Health

===== Physical/Chemical Properties =====

Boiling Pt:B.P. Text:176F,80C  
Vapor Pres:71  
Vapor D

ensity:2.5  
Spec Gravity:0.89  
Solubility in Water:INSOLUBLE  
Appearance and Odor:TAN LIQUID-KETONE ODOR  
Percent Volatiles by Volume:60

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES  
NONE  
Hazardous Decomposition Products:CARBON COMBUSTION PRODUCTS;NITROGEN  
COMPOUNDS

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE OR ALLOW SOLVENT TO EVAPORATE AND  
DISPOSE OF SOLIDS IN LAN  
DFILL

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular  
situation.