View NSN Online: https://aerobasegroup.com/nsn/8030-00-764-6658

FEL-PRO INCORPORATED -- FEL-PRO C-200 HIGH TEMPERATURE LUBRICANT -- 8030-00-764-6658

Product ID:FEL-PRO C-200 HIGH TEMPERATURE LUBRICANT MSDS Date:02/02/1987 FSC:8030 NIIN:00-764-6658 MSDS Number: BFNVM === Responsible Party === Company Name: FEL-PRO INCORPORATED Address:7450 N. MCCORMICK BLVD Box:C1103 City:SKOKIE State:IL ZIP:60076 Info Phone Num:(312) 674-77 00 OR (312) 761-4500 Emergency Phone Num: (312) 674-7700 OR (312) 761-4500 Preparer's Name: DIANE L. GALLAGHER CAGE:DO270 === Contractor Identification === Company Name: FEL-PRO INC DIV OF FELT PRODUCTS MFG CO Address:7450 N MCCORMICK Box:1103 City:SKOKIE State:IL ZIP:60076-4046 Country:US Phone:847-674-7700 OR 312-761-4500 CAGE:73165 Company Name: FEL-PRO INCORPORATED Address:7450 N MCCORMICK BLVD, BOX C1103 Box:C1103 City:SKOKIE State:IL ZIP:60076 Phone:312-674-7700/312-761-4500 CAGE:DO270

=====

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III) CAS:1330-20-7 RTECS #:ZE2100000 Fraction by Wt: 5 MG/CUM Routes of Entry: Inhalation:NO Skin:NO Ingestion:YES Reports of Carcinogenicity:NTP:NO IARC:NO OSHA:NO Health Hazards Acute and Chronic:NO ACUTE OR CHRONIC HEALTH HAZARDS KNOWN FOR PRODUCT. TOXICOLOGICAL STUDIES INDICATE PRODUCT IS NONIRRITATING TO SKIN OR EYES. PRODUCT CONTAINS INORGANIC LEAD. **Explanation of Carcin** ogenicity:NONE Effects of Overexposure:NONE EXPECTED First Aid: EYES: FLUSH WITH TEPID WATER 15 MINUTES, HOLDING EYELIDS APART, GET MEDICAL ATTENTION. SKIN: WASH WITH SOAP AND WATER. IF IRRITATION OCCURS, GET MEDICAL ATTENTION. INGESTION: CONTAINS INORGANIC LEAD M ONOXIDE; GET MEDICAL ATTENTION IMMEDIATELY. Flash Point Method: PMCC Flash Point:10 6F,41C Lower Limits: 1.0% Extinguishing Media: USE DRY CHEMICALS, FOAM, CO2, OR WATER FOG Fire Fighting Procedures: USE EYE PROTECTION. USE SCBA WHEN FIGHTING FIRES IN CONFINED AREAS. Unusual Fire/Explosion Hazard: IN THE PRESENCE OF OXYGEN, MATERIAL MAY DECOMPOSE TO FORM SULFUR OXIDES >750F. EXCEPT NOTED ABOVE, SAME AS PETROLEUM GREASE FIRES. Spill Release Procedures: REMOVE SOURCES OF IGNITION. WIPE UP WITH RAGS 0 R ABSORBENT MATERIAL. COMPLETE CLEAN-UP WITH DETERGENT & WATER OR HIGH FLASH POINT SOLVENT CLEANER WITH ADEQUATE VENTILATION. Handling and Storage Precautions: USE NORMAL STORAGE AND HANDLING. DO NOT EXPOSE TO HIGH HEAT, OPEN FLAMES OR STRONG OXIDIZERS. Other Precautions: PRODUCT CONTAINS HYDROCARBONS-DO NOT USE OXYGEN SERVICE. KEEP OUT OF REACH OF CHILDREN. ===== Exposure Controls/Personal Protection ====

## Eye Protection:SUFFICIENT TO PREVENT CONTACT. Work Hygienic Practices:USE GOOD HOUSEKEEPING PRACTICES. WASH THOROUGHLY BEFORE EATING, DRINKING OR SMOKING.

Supplemental Safety and Health

HCC:F4 Boiling Pt:B.P. Text:>500F Vapor Pres:NEGLIGIBLE Spec Gravity:1.45 Evaporation Rate & amp; Reference:(BUTYL ACETATE = 1): .75 Solubility in Water:NEGLIGIBLE Appearance and Odor:SOFT BLACK PASTE, CHARACTERISTIC AROMATIC ODO R

Stability Indicator/Materials to Avoid:YES AVOID STRONG OXIDIZERS Stability Condition to Avoid:NONE Hazardous Decomposition Products:PYROLYSIS YIELDS CO, CO2, INCOMPLETELY BURNED HYDROCARBONS, AND POSSIBLY SOX >750F

Waste Disposal Methods:USE CONTROLLED INCINERATION OR BURY IN A POSTED TOXIC SUSBSTANCES LANDFILL IN ACCORDANCE WITH FEDERAL, STATE AN

D

LOCAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies): This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.