

GC ELECTRONICS COMPANY -- 10-5002,RED INSULATOR -- 8040-00-779-2863

=====
Product Identification
=====

Product ID:10-5002,RED INSULATOR

MSDS Date:01/01/1985

FSC:8040

NIIN:00-779-2863

MSDS Number: BFPCM

=== Responsible Party ===

Company Name:GC ELECTRONICS COMPANY

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Info Phone Num:815-968-9661

Emergency Phone Num:815-96

8-9661

CAGE:EO032

=== Contractor Identification ===

Company Name:GC ELECTRONICS CO,SUB OF HOUSEHOLD INTERNATIONAL C

Address:1801 MORGAN ST

Box:1209

City:ROCKFORD

State:IL

ZIP:61105-1209

Country:US

Phone:815-968-9661

CAGE:EO032

Company Name:GC THORSEN

Address:1801 MORGAN STREET

Box:City:ROCKFORD

State:IL

ZIP:61105

Country:US

Phone:815-968-9661

CAGE:72653

=====
Composition/Information on Ingredients
=====

Ingred Name:LEAD (SARA III)

CAS:7439-92-1

RTECS #:OF7525000

OSHA PEL:0.0

5 MG/M3;1910.1025
ACGIH TLV:0.15 MG/M3;DUST 9192
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:COBALT (SARA III)
CAS:7440-48-4
RTECS #:GF8750000
OSHA PEL:0.1 MG/M3;AS CO
ACGIH TLV:0.05 MG/M3;DUST 9293

Ingred Name:MANGANESE (0.0007%)
ACGIH TLV:C,5 MG/CUM

Ingred Name:XYLENES (O-,M-,P- ISOMERS) (SARA III)
CAS:1330-20-7
RTECS #:ZE2100000
Fraction by Wt: 14.7%
OSHA PEL:100 PPM/150 STEL
ACGIH TLV:100 PPM/150STEL;9192
EPA Rpt Qty:1000 LBS
DOT Rpt Qty:1000 LBS

Ingred Name:NAPHTHA (PETROLEUM SPIRITS
OR BENZIN)
CAS:8030-30-6
RTECS #:SE7555000
Fraction by Wt: 33.7%
OSHA PEL:100 PPM

===== Hazards Identification =====

Effects of Overexposure:EYE/SKIN:IRRITATION. VAPORS:MILD
DRPRESSION,CONVULSION,LOSS OF CONSCIOUSNESS.

===== First Aid Measures =====

First Aid:EYE:FLUSH WITH WATER 15 MINUTES. SKIN:REMOVE CONTAMINATED
CLOTHING,WASH SKIN. INHALATION:REMOVE TO FRESH AIR,GIVE ARTIF RESP
IF NEEDED,CALL A PHYSICIAN

===== Fire Fighting Measures =====

Flash Point:50F/10C

Lower Limits:0.9

Upper Limits:6.0

Extinguishing Media:DRY CHEMICAL

Fire Fighting Procedures:WATER MAY BE INEFFECTIVE USE DRY CHEMICAL

Unusual Fire/Explosion Hazard:VAPORS IN EMPTY DRUMS MAY BE EXPLOSIVE

===== Accidental Release Measures =====

Spill Release Procedures:SECURE SOURCES OF IGNITION. AVOID BREATHING
VAPORS,CLEAN UP MATERIAL BY MIXING WITH SAND.PLACE IN DRUM AN

D
DISPOSE AS WASTE.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP FROM HEAT, SPARKS AND OPEN FLAME.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPROVED RESP DEVICE IN ACCORD WITH
EXPOSURE OF CONCERN.

Ventilation:LOCAL/MECHANICAL

Protective Gloves:RECOMMENDED

Eye Protection:SAFETY GLASSES

Supplemental Safety and Health

ADD INGREDIENT: ALCOHOL,1.48%,TLV: 1,000 (MFR); P
IGMENT (IRON

OXIDE,RESIN,ETC) 50%.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:23OF/110F

Vapor Density:4

Spec Gravity: