

PRODUCTS RESEARCH & CHEMICAL CORP. -- PR-1201-Q -- 5970-00-814-0394

=====  
Product Identification  
=====

Product ID:PR-1201-Q

MSDS Date:01/01/1985

FSC:5970

NIIN:00-814-0394

MSDS Number: BFQMY

=== Responsible Party ===

Company Name:PRODUCTS RESEARCH & CHEMICAL CORP.

Address:5430 SAN FERNANDO ROAD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Info Phone Num:818-240-2060

Emergency Phone Num:818-

240-2060

CAGE:DO563

=== Contractor Identification ===

Company Name:PRC-DESOTO INTERNATIONAL, INC. A PPG INDUSTRIES COMPANY

Address:5430 SAN FERNANDO RD

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Country:US

Phone:818-240-2060

CAGE:83574

Company Name:PRODUCTS RESEARCH & CHEMICAL

Address:NOW DBA COURTAULDS AEROSPACE

Box:1800

City:GLENDALE

State:CA

ZIP:91209

Phone:818-240-2060

CAGE:DO563

=====  
Composition/Information on Ingredients  
=====

Ingred Name:POLYSULFIDE POLYMER

Fraction by

Wt: 50%  
ACGIH TLV:UNKKNOWN

Ingred Name:PIGMENTS  
Fraction by Wt: 35%

Ingred Name:RESINS PLASTICIZERS  
Fraction by Wt: 3%

Ingred Name:TOLUENE (SARA III)  
CAS:108-88-3  
RTECS #:XS5250000  
Fraction by Wt: 4%  
Other REC Limits:NONE RECOMMENDED  
OSHA PEL:200 PPM; Z-2  
ACGIH TLV:S, 50 PPM; 9394  
EPA Rpt Qty:1000 LBS  
DOT Rpt Qty:1000 LBS

=====  
Hazards Identification  
=====

Effects of Overexposure:BASE COMPOUND MAY BE IRRITATING TO SKIN,EYES.

=====  
First Aid Measures  
=====

First Aid:SKIN:WASH THOROUGHLY WITH SOAP AND WATER.EYES;FLUSH THOROUGHLY WITH LARGE AMOUNTS OF WATER.INGESTION:INDUCE VOMITING.INHALATION:REMOVE TO FRESH AIR.GIVE CPR/OXYGEN IF NECESSARY.GET MEDICAL ATTENTION.

=====  
Fire Fighting Measures  
=====

Flash Point Method:PMCC  
Flash Point:>22.8C, 73.F  
Lower Limits:1.0  
Upper Limits:7.0  
Extinguishing Media:FOAM,DRY CHEMICAL,CARBON DIOXIDE.  
Fire Fighting Procedures:WEAR AIR-SUPPLIED RESPIRATOR WHILE FIGHTING FIRES.  
Unusual Fire/Explosion Hazard:EMISSION OF TOXIC VAPORS.

=====  
Accidental Release Measures  
=====

Spill Release Procedures:STOP LEAK AT SOURCE.ELIMINATE IGNITION SOURCES.ABSORB EXCESS WITH RAGS,PAPER TOWELS OR OTHER ABSORBENT MATERIAL.CLEAN AREA WITH XYLENE OR TOLUENE.PLACE IN CLOSED CONTAINERS.

=====  
Handling and Storage  
=====

Handling and Storage Precautions:KEEP IN C

LOSED CONTAINERS AT ROOM  
TEMPERATURE.AVOID FIRE HAZARDS.PROTECT FROM PHYSICAL DAMAGE.AVOID  
ACCELERATOR SPILLAGE.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:AIR SUPPLIED RESPIRATOR RECOMMENDED IN CONFINED  
AREAS.

Ventilation:MECHANICAL/LOCAL EXHAUST.TO MINIMIZE SOLVENT VAPOR BELOW  
TLV

Protective Gloves:POLYETHYLENE

Eye Protection:CHEM GOGGLES

Other Protective Equipment:USE PROTECTIVE HAND CREAM.

Supplemental Safety and Health

KEY1:F

3.

===== Physical/Chemical Properties =====

HCC:D1

Spec Gravity:1.7

Solubility in Water:NEGLIGIBLE

Appearance and Odor:PINKSIH-BROWN SYRUP;SLIGHT TOLUENE ODOR.

Percent Volatiles by Volume:6

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

DECOMPOSES WHEN EXPOSED TO STRONG OXIDIZING AGENTS.

Stability Condition to Avoid:AVOID IGNITION SOURCES

Hazardous Decomposition Products:OXIDES OF SULFUR;HYDROGEN

SULFIDE;FORMIC ACID.

===== Disposal Considerations =====

Waste Disposal Methods:PLACE ABSORBED MATL IN CLOSED CONTAINERS AND  
DISPOSE IN ACCORDANCE WITH LOCAL,STATE AND FEDERAL REGULATIONS.DO  
NOT INCINERATE.

Disclaimer (provided with this information by the compiling agencies):  
This information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this inf

ormation to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.