

CON-LUX COATINGS,INC. -- ALKYD,FLAT BEIGE 30450 -- 8010-00-823-8012

=====
Product Identification
=====

Product ID:ALKYD,FLAT BEIGE 30450

MSDS Date:01/01/1987

FSC:8010

NIIN:00-823-8012

MSDS Number: BFRDF

=== Responsible Party ===

Company Name:CON-LUX COATINGS,INC.

Address:226 TALMADGE ROAD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Info Phone Num:201-287-4000

Emergency Phone Num:201-287

-4000

CAGE:60189

=== Contractor Identification ===

Company Name:CON-LUX COATINGS INC

Address:226 TALMADGE RD

Box:847

City:EDISON

State:NJ

ZIP:08818-0847

Country:US

Phone:732-287-4000

CAGE:60189

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: 31%

OSHA PEL:100 PPM

Ingred Name:TITANIUM DIOXIDE

CAS:13463-67-7

RTECS #:XR2275000

OSHA PEL:15 MG/M3 TDUST

ACGIH TLV:10 MG/M3 TDUST; 929

===== Hazards Identification =====

Effects of Overexposure:IRRITATION OF EYES AND SKIN.IRRITATION OF
RESPIRATORY TRACT HEADACHE OR DIZZINESS.

===== First Aid Measures =====

First Aid:SKIN/EYES:FLUSH W/PLENTY OF WATER. INHAL:MOVE TO FRESH AIR.
CALL DR.IF IRRITATION PERSISTS.

===== Fire Fighting Measures =====

Flash Point:128F,53C

Extinguishing Media:USE CLASS B EXTINGUISHERS (
CARBON DIOXIDE, DRY
CHEMICAL,FOAM)

Fire Fighting Procedures:USE WATER TO COOL CLOSED CONTAINERS & PREVENT
AUTOIGNITION.

Unusual Fire/Explosion Hazard:KEEP CONTAINERS TIGHTLY CLOSED AND
ISOLATE FROM SOURCES OF IGNITION.

===== Accidental Release Measures =====

Spill Release Procedures:REMOVE ALL SOURCES OF IGNITION(FLAMES,HOT
SURFACES,ELECTOR FRICTIONAL SPARKS,HOT SURFACES)AVOID BREATHING
VAPORS. VENTILATE AREA.REMOVE WITH INERT ABSORBENT AND NON-SP
ARKING
TOOLS.

===== Handling and Storage =====

Handling and Storage Precautions:DO NOT STORE AT ELEVATED TEMP.KEEP
AWAY FROM OPEN FLAMES AND SPARKS.

Other Precautions:DO NOT TAKE INTERNALLY.CONTAINERS SHOULD BE GROUNDED
WHEN POURING.AVOID PROLONGED OR REPEATED CONTACT WITH SKIN.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:BUREAU OF MINES APPROVED CHEM/MECH FILTER
RESPRATOR

Ventilation:LOCAL EXHA

UST
Protective Gloves: YES
Eye Protection: SAFETY GLASSES OR GOGGLES
Other Protective Equipment: PREVENT PROLONGED SKIN CONTACT WITH
CONTAMINATED CLOTHING.

Supplemental Safety and Health
CLOSED CONTAINERS MAY EXPLODE WHEN EXPOSED TO EXTREME HEAT. DO NOT APPLY
TO HOT SURFACES.

===== Physical/Chemical Properties =====

HCC: F4
Boiling Pt: B.P. Text: 174F, 79C
Vapor Pres: 4
Vapor Density: 5.3
Spec Gravity: 1.37
Evaporation Rate & Reference: BUAC = 1: 0.05
Solubility in
Water: NEGLIGIBLE
Appearance and Odor: BEIGE LIQUID, MILD ALIPHATIC ODOR.
Percent Volatiles by Volume: 57

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid: YES
Hazardous Decomposition Products: CO, CO*2

===== Disposal Considerations =====

Waste Disposal Methods: DISPOSE OF IN ACCORDANCE WITH LOCAL, STATE AND
FEDERAL REGULATIONS. DO NOT INCINERATE CLOSED CONTAINERS.

Disclaimer (provided with this information
by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume responsibility for the suitability of this information to their
particular situation.