

MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION -- ETHYLENE GLYCOL -- 6810-00-825-7472

=====  
Product Identification  
=====

Product ID:ETHYLENE GLYCOL

MSDS Date:01/01/1987

FSC:6810

NIIN:00-825-7472

MSDS Number: BFRJK

=== Responsible Party ===

Company Name:MALLINCKRODT INC.,SCIENCE PRODUCTS DIVISION

Emergency Phone Num:314 982 5000

CAGE:62910

=== Contractor Identification ===

Company Name:MALLINCKRODT SP

ECIALTY CHEMICALS CO

Address:222 RED SCHOOL LANE

Box:City:PHILLIPSBURG

State:NJ

ZIP:08865

Country:US

Phone:908-859-2151

CAGE:62910

=====  
Composition/Information on Ingredients  
=====

Ingred Name:ETHYLENE GLYCOL (SARA III)

CAS:107-21-1

RTECS #:KW2975000

Fraction by Wt: >99%

OSHA PEL:C 50 PPM

ACGIH TLV:C 50 PPM,VAPOR; 9192

EPA Rpt Qty:1 LB

DOT Rpt Qty:1 LB

=====  
Hazards Identification  
=====

Effects of Overexposure:INH:DIZZ,HEAD,PULMONARY EDEM

A;ING:CAUSES

VOMIT,HEAD,LOW BLD PR;EYES/SKIN:MINOR/SEVERE IRRITATION.

=====  
First Aid Measures  
=====

First Aid:INHAL:RMV TO FRESH AIR.GIVE CPR/OXYGEN IF BREATHING IS  
DIFFICULT.GET MD;INGEST:IMMED INDUCE VOMIT BY GIVING 2 GL OF  
WATER.NOTHING BY MOUTH IF UNCONSCIOUS.GET MD IMMED;SKIN/EYES:FLUSH  
IMMED W/LG QTY H\* 20 FOR 15 MIN.RMV CONTMNTD CLOTHES.GET MED ATTN.

=====  
Fire Fighting Measures  
=====

Flash Point:

110C(230F)

Lower Limits:3.2

Upper Limits:15.3

Extinguishing Media:ALCOHOL FOAM,WATER,CO\*2,DRY CHEMICAL.WATER/FOAM MAY FROTH.

Fire Fighting Procedures:WEAR SELF-CNTD BRTHG,APP H\*20 SPRAY TO COOL CONTR.

Unusual Fire/Explosion Hazard:MODERATE HAZARD WHEN EXPOSED TO HEAT OR FLAME

===== Accidental Release Measures =====

Spill Release Procedures:VENTILATE AREA OF SPILL.CLEAN UP PERSONS NEED PROTCTV CLOTHG/RESP PROTCTION FM VAP.COLLECT LIQUID & PLACE IN A

SUITABLE CONTAINER FOR RECOVERY OR DISPOSAL.WASH RESIDUE & SMALL SPILLS TO SEWER W/COPIOU S AMTS OF WATER.REMOVE ALL SOURCES OF IGNITION.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP IN TIGHTLY CLOSED CONTNRS AT COOL,DRY, VENTILATED PLACE. PROTECT AGAINST PHY DAMAGE.

Other Precautions:AVOID BREATHING MIST.USE W/ADEQUATE VENTILATION.KEEP CONTAINERS CLOSED.WASH THOROUGHLY AFTER HANDLING.AVOID SKIN,EYES & CLOTHING CONTACT.DO NOT EAT IN WORK AREA.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:FULL FACE RESPIRATOR

Ventilation:LOCAL EXHAUST TO MAINTN BELOW TLV.

Protective Gloves:IMPERVIOUS

Eye Protection:GOGGLES/FACE SHIELD

Other Protective Equipment:FULL PROTECTIVE CLOTHING,SAFETY SHOWER,EYE WASH STATION

Supplemental Safety and Health

MSDS FROM MFR DATED 01/28/85,CONFORMS TO OSHA HAZ COMM STD; SP GRAVITY RANGE:1.112-1.115

===== Physical/

Chemical Properties =====

HCC:V5

Boiling Pt:B.P. Text:193C(379F)

Vapor Pres:.05

Vapor Density:2.14

Spec Gravity:1.1135

Evaporation Rate & Reference:1.0(CCL\*4=1)

Solubility in Water:COMPLETE

Appearance and Odor:COLORLESS LIQID.ODORLESS

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

STRONG OXIDIZERS,CORROSIVE MATL;OLEUM,H\*2SO\*4,HCL\*4,ETC.

Stability Condition to Avoid:IGNITION & MOISTURE SOURCES.

Hazardous Decompos

ition Products:OXIDES OF NITROGEN & CARBON WHEN

IGNITED IN AIR.

===== Disposal Considerations =====

Waste Disposal Methods:WHATEVER CANNOT BE SAVED FOR RECLAMATION MAY BE  
DISPOSD AS HAZ WASTE IN A RCRA APPRVD WASTE DISPOSAL FACILITY OR  
MIX WITH A MORE FLAMMABLE SOLVENT AND ATOMIZE IN AN APPROVED  
INCINERATION.ENSURE COMPLI ANCE W/LOCAL,,STATE, & FEDERAL  
REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):

This

information is formulated for use by elements of the Department  
of Defense. The United States of America in no manner whatsoever,  
expressly or implied, warrants this information to be accurate and  
disclaims all liability for its use. Any person utilizing this  
document should seek competent professional advice to verify and  
assume responsibility for the suitability of this information to their  
particular situation.