

STEVEN INDUSTRIES -- MMM-A-121,NEOPRENE CONTACT CEMEN -- 8040-00-832-6173

=====
Product Identification
=====

Product ID:MMM-A-121,NEOPRENE CONTACT CEMEN

MSDS Date:01/01/1985

FSC:8040

NIIN:00-832-6173

MSDS Number: BFRQS

=== Responsible Party ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Info Phone Num:201-437-6501

Emergency Phone Num:2

01-437-6501

CAGE:33150

=== Contractor Identification ===

Company Name:STEVEN INDUSTRIES

Address:39 AVENUE C

Box:8

City:BAYONNE

State:NJ

ZIP:07002-3417

Country:US

Phone:201-437-6501

CAGE:33150

=====
Composition/Information on Ingredients
=====

Ingred Name:PHENOLIC RESIN

Fraction by Wt: 6%

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 14%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

Ingred Name:HEX

ANE (N-HEXANE)
CAS:110-54-3
RTECS #:MN9275000
Fraction by Wt: 41%
OSHA PEL:500 PPM
ACGIH TLV:50 PPM; 9293
EPA Rpt Qty:1 LB
DOT Rpt Qty:1 LB

Ingred Name:ACETONE (SARA III)
CAS:67-64-1
RTECS #:AL3150000
Fraction by Wt: 19%
OSHA PEL:1000PPM
ACGIH TLV:750PPM/1000STEL;9293
EPA Rpt Qty:5000 LBS
DOT Rpt Qty:5000 LBS

Ingred Name:METHYL ETHYL KETONE (2-BUTANONE) (MEK) (SARA III)
CAS:78-93-3
RTECS #:EL6475000
Fraction by Wt: 8.2%
OSHA PEL:200 PPM/300 STEL
ACGIH TLV:200 PPM/300STEL 9192
EPA Rpt Qty:500
0 LBS
DOT Rpt Qty:5000 LBS

=====
===== Hazards Identification =====
=====

Effects of Overexposure:NARCOSIS AND/OR POSSIBLE HEADACHE OR BRONCHIAL
CATARRH

=====
===== First Aid Measures =====
=====

First Aid:INHALATION:MOVE TO FRESH AIR. SEE DOCTOR

=====
===== Fire Fighting Measures =====
=====

Flash Point:15F TCC
Lower Limits:1.2
Upper Limits:13
Extinguishing Media:DRY CHEM, CO*2, FOAM
Fire Fighting Procedures:SELF-CO

CONTAINED BREATHING APPARATUS SHOULD BE WORN

Unusual Fire/Explosion Hazard:KEEP AWAY FROM OPEN FLAME,SPARKS, HOT SURFACES & OXIDIZERS.

===== Accidental Release Measures =====

Spill Release Procedures:WIPE UP

===== Handling and Storage =====

Handling and Storage Precautions:STORE IN SOLVENT STORAGE AREA. DO NOT STORE NEAR HEAT OR IN DIRECT SUNLIGHT.

===== Exposure Controls/Personal Protection =====

Pr

Protective Gloves:YES

Eye Protection:SAFETY GLASSES

Other Protective Equipment:HAND CREAM

Supplemental Safety and Health

PRODUCT ALSO CONTAINS 1% METALLIC OXIDES AND 11% VEHICLE.

===== Physical/Chemical Properties =====

HCC:F2

Boiling Pt:B.P. Text:132F

Vapor Pres:185

Vapor Density:0.75

Spec Gravity:0.8

Evaporation Rate & Reference:SLOWER THAN ETHER

Appearance and Odor:OFF WHITE,KETONE & NAPHTHA ODOR

Percent Volatiles by Volume:88

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS

Hazardous Decomposition Products:HCL, PHENOL, CO, CO*2, AMMONIA, CHLORINE GAS

===== Disposal Considerations =====

Waste Disposal Methods:SOLVENT DISPOSAL PROCEDURES IN ACCORDANCE W/LOCAL,STATE,& FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department of Defense

e. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.