

STEVEN INDUSTRIES -- TECTYL 894 -- 8030-00-837-6557

=====
Product Identification
=====

Product ID:TECTYL 894
MSDS Date:01/01/1987
FSC:8030
NIIN:00-837-6557
MSDS Number: BFRWV
=== Responsible Party ===
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Info Phone Num:201-437-6501
Emergency Phone Num:201-437-6501
CAGE:33150
=== Contractor Identifi
fication ===
Company Name:STEVEN INDUSTRIES
Address:39 AVENUE C
Box:8
City:BAYONNE
State:NJ
ZIP:07002-3417
Country:US
Phone:201-437-6501
CAGE:33150

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL SPIRITS
RTECS #:SE7550000
ACGIH TLV:500 PPM

Ingred Name:100 PALE OIL
ACGIH TLV:5 MG/CUM

=====
Hazards Identification
=====

Effects of Overexposure:EYES-SEVERE IRRITATION. SKIN-DEFATTING;
DERMATITIS. INHALATION-IRRITATION

; DIZZINESS AND NAUSEA.

=====
===== First Aid Measures =====

First Aid:SKIN-WASH WITH SOAP AND WATER. REMOVE CONTAMINATED CLOTHING-WASH BEFORE REUSE. EYES-FLUSH WITH LARGE AMOUNTS OF WATER.SWALLOWING-DO NOT INDUCE VOMITING-CALL PHYSICIAN. IF BREATHING DIFFICULT,ADMINISTER OXYGEN. APPLY ARTIFICIAL RESPIRATION IF NEEDED.

=====
===== Fire Fighting Measures =====

Flash Point:100F; 38C CC

Lower Limits:0.8

Extinguishing Media:

DRY CHEMICAL, FOAM, CO2

Fire Fighting Procedures:SELF-CONTAINED WITH FACE PIECE-POSITIVE PRESSURE MODE

Unusual Fire/Explosion Hazard:VAPORS HEAVIER THAN AIR AND MAY TRAVEL ALONG GROUND. RESIDUE IN EMPTY DRUM CAN IGNITE.

=====
===== Accidental Release Measures =====

Spill Release Procedures:SMALL-ABSORB ON ABSORBENT MATERIAL AND TRANSFER TO HOOD. LARGE-STOP SPILL AT SOURCE; DIKE AREA; PUMP LIQUID TO SALVAGE TANK. REMAINING MATERIAL MAY BE ABSORBED ON SAND OR CLAY AND SHOVELED INTO CONTAINERS.

=====
===== Handling and Storage =====

Handling and Storage Precautions:ALL HAZARD PRECAUTIONS SHOULD BE APPLIED TO EMPTIED CONTAINER SINCE RESIDUE REMAINS.

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:SELF-CONTAINED APPARATUS WITH FACEPIECE IF TLV EXCEEDED

Ventilation:LOCAL AND MECHANICAL

Protective Gloves:IMPERMEABLE

Eye Protection:CHEMICAL SPLASH GOGGLES

Other

Protective Equipment: IMPERVIOUS CLOTHING AND BOOTS SHOULD BE WORN.

Supplemental Safety and Health

% MINERAL SPIRITS: 30-60

% 100 PALE OIL: 10-30

===== Physical/Chemical Properties =====

HCC:F3

Boiling Pt: B.P. Text: 300F; 149C

Vapor Pres: 2

Vapor Density: >1

Spec Gravity: 0.87

Evaporation Rate & Reference: < ETHER

Solubility in Water: NA

Appearance and Odor: NA

Percent Volatiles by Volume: 30

===== Stability and Reactivity Data =====

=====

Stability Indicator/Materials to Avoid: YES

STRONG OXIDIZING AGENTS

Hazardous Decomposition Products: CO, CO*2; VARIOUS HYDROCARBONS AND SULFUR COMPOUNDS.

===== Disposal Considerations =====

Waste Disposal Methods: SMALL-VOLATILE PORTION TO EVAPORATE IN HOOD.

DESTROY REMAINING MATERIAL BY BURNING IN AN IRON PAN. LARGE-DESTROY BY LIQUID INCINERATION.

Disclaimer (provided with this information by the compiling agencies):

This information is

formulated for use by elements of the Department

of Defense. The United States of America in no manner whatsoever,

expressly or implied, warrants this information to be accurate and

disclaims all liability for its use. Any person utilizing this

document should seek competent professional advice to verify and

assume responsibility for the suitability of this information to their

particular situation.