

ASHLAND OIL INC. -- TECTYL 894 -- 8030-00-837-6557

=====
Product Identification
=====

Product ID:TECTYL 894
MSDS Date:01/01/1985
FSC:8030
NIIN:00-837-6557
MSDS Number: BFRWW
=== Responsible Party ===
Company Name:ASHLAND OIL INC.
Emergency Phone Num:614-790-3333
CAGE:81355
=== Contractor Identification ===
Company Name:ASHLAND INC
Address:1409 WINCHESTER AVE
Box:391
City:ASHLAND
State:KY
ZIP:4111
4
Country:US
Phone:800-622-6846
CAGE:81355

=====
Composition/Information on Ingredients
=====

Ingred Name:SOLVENTS
Fraction by Wt: 40%
ACGIH TLV:500PPM

Ingred Name:PETROLEUM OIL
Fraction by Wt: 20%
ACGIH TLV:5MG/CUM OILMIST

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE IRRITATION;EXCESSIVE INHALATION MAY
CAUSE DIZZINESS,NAUSEA,VOMITING,HEADACHES.

=====
First Aid Measures
=====

==

First Aid:FLUSH EYES WITH WATER,FLUSH SKIN WITH SOAP AND WATER.IF SWALLOWED,DO NOT INDUCE VOMITING.

=====
===== Fire Fighting Measures =====

Flash Point:105F 41C CC
Lower Limits:1.0
Upper Limits:6.0
Extinguishing Media:CO2,FOAM,DRY CHEMICAL
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE IGNITION SOURCE,STOP SPILL AT SOURCE,CONTAIN SPILL BY DIKE,ETC.,PUMP INTO SALVAGE TANK.

=====
===== Handling and Storage =====

Handling and Storage Precautions:AVOID CONTACT WITH EYES AND PROLONGED CONTACT WITH SKIN. AVOID BREATHING VAPOR. WASH AFTER HANDLING.
Other Precautions:NONE

=====
===== Exposure Controls/Personal Protection =====

Respiratory Protection:NONE REQUIRED
Ventilation:SPECIAL VENT.AS REQ'D TO MAINTAIN LEVEL BELOW OSHA ESTABLISHED TLV
Protective Gloves:LONG GLOVES
Eye Protection:
n:SAFETY GLASSES
Supplemental Safety and Health

=====
===== Physical/Chemical Properties =====

HCC:F4
Boiling Pt:B.P. Text:310F
Vapor Pres:UNK
Vapor Density:>1
Spec Gravity: