

ESSEX CHEM CORP, SPECIALTY CHEM DIV -- PRO-SEAL 890 BASE, CLASS A -- 8030-00-841-6832

=====
Product Identification
=====

Product ID:PRO-SEAL 890 BASE, CLASS A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-841-6832

MSDS Number: BFSCS

=== Responsible Party ===

Company Name:ESSEX CHEM CORP, SPECIALTY CHEM DIV

Address:19451 SUSANA RD

City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:KO319

=== Contractor I

dentification ===

Company Name:ESSEX CHEM CORP, SPECIALTY CHEM DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

CAGE:KO319

Company Name:ESSEX CHEMICAL CORP PRO-SEAL DIV

Address:19451 SUSANA RD

Box:City:COMPTON

State:CA

ZIP:90221-5713

Country:US

Phone:310-537-7600

CAGE:83527

=====
Composition/Information on Ingredients
=====

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty

:1000 LBS
DOT Rpt Qty:1000 LBS

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SKIN IRRIT. INH MAY LEAD TO NARCOSIS

=====
First Aid Measures
=====

First Aid:WASH THOROUGHLY AFTER HANDLING. FOR INH REMOVE TO FRESH AIR.
IF INGESTED, CONSULT MD IMMED. FLUSH EYES W/WATER COPIOUSLY.

=====
Fire Fighting Measures
=====

Flash Point:68F CC
Lower Limits:1.3
Upper Limits:
6.8
Extinguishing Media:CO*2, FOAM, DRY CHEM
Fire Fighting Procedures:WATER NOT REC
Unusual Fire/Explosion Hazard:VOLATILE SLVNT

=====
Accidental Release Measures
=====

Spill Release Procedures:WIPE UP W/SLVNT & RAGS, MFR REC

=====
Handling and Storage
=====

Handling and Storage Precautions:STORE IN CLOSED CNTNRS BELOW 80F.
AVOID OPEN FLAMES, ELECTRICAL SPARKS WHEN USING.
Other Precautions:RED LABEL MATL

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:USE W/ADEQUATE VENT
Ventilation:MECH, DESIRABLE
Protective Gloves:REC
Eye Protection:REC
Other Protective Equipment:APRON, COVERALLS
Supplemental Safety and Health
BP GIVEN FOR SLVNT. 1 GAL SIZE, 2 HR APPLICATION TIME, & BRUSH
APPLICATION.KEY1:F3.

=====
Physical/Chemical Properties
=====

HCC:F3
Boiling Pt:B.P. Text:230F
Vapor Pres:37
Vapor Density:3.1
Spec Gravity:1.5
Evaporation Rate &

Reference:4.5 ETHYLETHER

Solubility in Water:NIL

Appearance and Odor:WHITE SEMI-SOLID FLUID, SULFIDE ODOR

Percent Volatiles by Volume:15

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

AVOID STRONG OXIDIZING AGENTS

Hazardous Decomposition Products:CO*2, H*2O, SO*2 UPON COMBUSTIION

===== Disposal Considerations =====

Waste Disposal Methods:BURN WASTE, MFR REC

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department of Defense. The United States of America in no manner whatsoever, expressly or implied, warrants this information to be accurate and disclaims all liability for its use. Any person utilizing this document should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.