

AMERICAN LACQUER SOLVENTS CO -- 125-880 WASH PRIMER, PT A -- 8030-00-850-7076

=====
Product Identification
=====

Product ID:125-880 WASH PRIMER, PT A

MSDS Date:01/01/1985

FSC:8030

NIIN:00-850-7076

MSDS Number: BFSPR

=== Responsible Party ===

Company Name:AMERICAN LACQUER SOLVENTS CO

Address:PO BOX 803

City:VALLEY FORGE

State:PA

ZIP:19482-0803

Country:US

Emergency Phone Num:813-236-5594

CAGE:91470

=== Contractor Identification ===

Company Name:AMERICAN LACQUER SOLVENTS CO

Address:PO BOX 803

Box:City:VALLEY FORGE

State:PA

ZIP:19482-0803

Country:US

CAGE:91470

=====
Composition/Information on Ingredients
=====

Ingred Name:ZINC CHROMATE

CAS:13530-65-9

RTECS #:GB3290000

OSHA PEL:0.1 MG/M3 (CRO3)

ACGIH TLV:0.01MG/M3(CR)A1;9192

Ingred Name:MAGNESIUM SILICATE(TALC); NON-ASBESTOS. TLV IS FOR
RESPIRABLE DUST

ACGIH TLV:2 MG/CUM, TALC

Ingred Name:VINYL RESIN

Fraction by Wt:

9.2%

Ingred Name:ISOPROPYL ALCOHOL (SARA III)

CAS:67-63-0

RTECS #:NT8050000

Fraction by Wt: 64.4%

OSHA PEL:400 PPM/500 STEL

ACGIH TLV:400 PPM/500STEL;9192

Ingred Name:TOLUENE (SARA III)

CAS:108-88-3

RTECS #:XS5250000

Fraction by Wt: 16.5%

OSHA PEL:200 PPM/150 STEL

ACGIH TLV:50 PPM; 9293

EPA Rpt Qty:1000 LBS

DOT Rpt Qty:1000 LBS

===== Hazards Identification =====

Effects of Overexposure:SKIN:DRYING.EYES:IRRIT.INH:ANESTHESIA, HDCH,
DIZZ, NAUS, UPPER RES
PIRATION IRRITATION.

===== First Aid Measures =====

First Aid:INH:MOVE TO FRESH AIR, GIVE ART RESP IF NEC. CALL MD.
SKIN:WASH W/MILD SOAP & WATER,APPLY MILK SKIN CREAM. CALL MD IF
SEVERE. EYES:FLUSH W/WATER 15 MINS CALL MD. ING:INDUCE VOMITING,
CALL MD.

===== Fire Fighting Measures =====

Flash Point:45F,7.2C TOC

Lower Limits:1.0

Upper Limits:7.0

Extinguishing Media:FOAM, CO*2, DRY CHEMICAL, WATER SPRAY

Fire F

ighting Procedures:SMALL FIRE:USE CO*2/DRY CHEM. LARGER

FIRE:ALCOHOL TYPE FOAM.

Unusual Fire/Explosion Hazard:HAZARDOUS WHEN EXPOSED TO HEAT & OPEN
FLAMES.

===== Accidental Release Measures =====

Spill Release Procedures:ELIMINATE ALL SOURCES OF IGNITION. FLUS
HEAVILY WITH WATER.

===== Handling and Storage =====

Handling and Storage Precautions:KEEP COOL & AWAY FROM SOURCES OF
IGNITION. USE WITH ADEQUATE VENTILATI

ON. AVOID PROLONGED OR
REPEATED PERSONAL CONTACT.

===== Exposure Controls/Personal Protection =====

Respiratory Protection:NIOSH/MSHA APPRVD RESP FOR EXPLOSURE OF CONCERN.
Ventilation:ADEQUATE TO MAINTAIN LEVELS BELOW TLV.
Protective Gloves:IMPERMEABLE
Eye Protection:FACE SHIELD-CHEM GOGGLES
Other Protective Equipment:APRON,BARRIER CREAM
Supplemental Safety and Health
ADDRESS:2601 E.HENRY AVE, TAMPA, FLA 33610. CONFORMS TO MIL-P-15328B.
PT OF A 2 PART KIT. PT B IS
125-880C CATALYST. ADDTNL
INGRED:11-25 PAINT ADDITIVE. 1.3% BP:110-112C. KEY1:J1.

===== Physical/Chemical Properties =====

HCC:F2
Boiling Pt:B.P. Text:230-233F
Spec Gravity:0.9000

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES
Stability Condition to Avoid:HEAT, SPARKS, OPEN FLAME,FIRE

===== Disposal Considerations =====

Waste Disposal Methods:INCINERATE UNDER S
AFE CONDITIONS OR DISPOSE IN
ACCORDANCE W/LOCAL, STATE & FEDERAL REGULATIONS.

Disclaimer (provided with this information by the compiling agencies):
This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
document should seek competent professional advice to verify and
assume

responsibility for the suitability of this information to their particular situation.