

DOW CORNING CORP. -- A-4014 PRIMER -- 8040-00-855-0779

=====
Product Identification
=====

Product ID:A-4014 PRIMER

MSDS Date:01/01/1985

FSC:8040

NIIN:00-855-0779

MSDS Number: BFSWJ

=== Responsible Party ===

Company Name:DOW CORNING CORP.

Address:3901 SOUTH SAGINAW ROAD

Box:997

City:MIDLAND

State:MI

ZIP:48640

Country:US

Info Phone Num:517-496-5900

Emergency Phone Num:517-496-5900

CAGE:5D028

=== Co

ntractor Identification ===

Company Name:DOW CORNING CORP

Address:3901 S SAGINAW RD

Box:997

City:MIDLAND

State:MI

ZIP:48686-0997

Country:US

Phone:517-496-6000/517-496-6315

CAGE:5D028

Company Name:DOW CORNING CORP

Address:2200 W SALZBURG RD

Box:City:AUBURN

State:MI

ZIP:48611

Country:US

Phone:517-496-4388

CAGE:71984

=====
Composition/Information on Ingredients
=====

Ingred Name:NAPHTHA (PETROLEUM SPIRITS OR BENZIN)

CAS:8030-30-6

RTECS #:SE7555000

Fraction by Wt: >80%.

OSHA PEL:

100 PPM

=====
Hazards Identification
=====

Effects of Overexposure:MAY CAUSE SLIGHT ANESTHESIA,HEADACHE,ETC;

=====
First Aid Measures
=====

First Aid:INHAL:MOVE TO FRESH AIR. CALL DR. SKIN & EYES:FLUSH WITH WATER.

=====
Fire Fighting Measures
=====

Flash Point:50F OC
Lower Limits:1.2.
Upper Limits:6.0.
Extinguishing Media:CO*2 OR FOAM
Fire Fighting Procedures:NONE
Unusual Fire/Explosion Hazard:NONE

=====
Accidental Release Measures
=====

Spill Release Procedures:MOP,WIPE OR SOAK UP WITH ABSORBENT MATERIAL USING PROPERE PROTECTIVE EQUIPMENT.

=====
Handling and Storage
=====

Handling and Storage Precautions:WEAR RUBBER GLOVES,FULL PROTECTIVE CLOTHING & SELF-CONTAINED BREATHING APPARATUS

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:ORGANIC VAPOR TYPE
Ventilation:MECHANICAL IS RECOMMENDED
Protective Gloves:RUBBER OR PLAST
Eye Protection:SAFETY GLASSES
Other Protective Equipment:AS REQUIRED BY THE USER
Supplemental Safety and Health

=====
Physical/Chemical Properties
=====

HCC:F2
Boiling Pt:B.P. Text:210F APPROX
Vapor Pres:25
Vapor Density:>1.0
Spec Gravity:0.9
Evaporation Rate & Reference: