

PARR,INC. SUB OF KOPPERS CO. -- PLASTILUBE MOLY 3 -- 8030-00-862-8356

=====
Product Identification
=====

Product ID:PLASTILUBE MOLY 3

MSDS Date:01/01/1987

FSC:8030

NIIN:00-862-8356

MSDS Number: BFTCT

=== Responsible Party ===

Company Name:PARR,INC. SUB OF KOPPERS CO.

Address:5151 DENNISON AVENUE

City:CLEVELAND

State:OH

ZIP:44101

Country:US

Info Phone Num:216-651-2010

Emergency Phone Num:216-651-

2010

CAGE:77163

=== Contractor Identification ===

Company Name:PARR,INC. SUB OF KOPPERS CO.

Address:5151 DENNISON AVENUE

Box:City:CLEVELAND

State:OH

ZIP:44101

Country:US

Phone:216-651-2010

CAGE:77163

Company Name:THIEM CORP SUB OF KOPPERS CO INC

Address:5151 DENISON AVE

Box:93019

City:CLEVELAND

State:OH

ZIP:44101-5019

Country:US

Phone:216-651-2010

CAGE:70904

=====
Composition/Information on Ingredients
=====

Ingred Name:MINERAL OIL (EXPOSURE REGULATED AS 'OIL MIST')

CAS:8012-

95-1
RTECS #:PY8030000
Fraction by Wt: UNK
OSHA PEL:5 MG/M3
ACGIH TLV:5 MG/M3/10 STEL;9192

Ingred Name:MOLYBDENUM DISULFIDE
CAS:1317-33-5
RTECS #:QA4697000
Fraction by Wt: UNK
OSHA PEL:10 MG/M3 TDUST (MO)
ACGIH TLV:10 MG/M3 (MO); 8990

Ingred Name:ORGANOPHYLLIC THICKENING AGENT (CLAY)
Fraction by Wt: UNK

=====
Hazards Identification
=====

Effects of Overexposure:MFR. STATES: "NIL OR NONE"

=====
First Aid Measures
=====

First Aid:WASH SKIN THOROUGHLY AFTER PROLONGED & REPEATED CONTACT
W/SKIN; EYE CONTACT: FLOOD W/WATER; INGEST: CONSULT PHYSICIAN.

=====
Fire Fighting Measures
=====

Flash Point:>400F/>204.4CTOC
Fire Fighting Procedures:NONE -CARBON DIOXIDE IS BEST; TREAT AS CLASS
"B" FIRE
Unusual Fire/Explosion Hazard:MFR STATES: "NONE"

=====
Accidental Release Measures
=====

Spill Release Procedures:COLLECT SPILLED MATERIAL. RINSE FLOOR
W/APPROPRIATE & APPROVED DEGREASING SOLVENT, ABSORB UNTO INERT
MATERIAL. WASH FLOOR DOWN W/WARM SOAPY WATER. PUT MATERIAL INTO
CONTAINERS SUITABLE FOR SHIPMENT TO DISPOSAL AREA.

=====
Handling and Storage
=====

Handling and Storage Precautions:KEEP CONTAINERS CLOSED. AVOID
EXCESSIVE HEAT (>500F) & OPEN FLAME.

=====
Exposure Controls/Personal Protection
=====

Respiratory Protection:MFR STATES: "NONE"
Ventilation:AS REQUIRED T

O MAINTAIN CONC. BELOW THE SUGGESTED TLV

Protective Gloves:OIL-PROOF TYPE

Eye Protection:PROTECTIVE GOGGLES

Other Protective Equipment:AS REQUIRED FOR TASK @ HAND.

Supplemental Safety and Health

COMPANY HAS PASSED THROUGH SEVERAL OWNERS AND IS CURRENTLY (DEC92)
OWNED BY KOPPERS. SEE CAGES 02307, 70904, AND 77163.

===== Physical/Chemical Properties =====

HCC:N1

Boiling Pt:B.P. Text:>500F/>260C

Spec Gravity:0.90

Solubility in Water:NIL

Percent Volatiles by Volume:

NIL

===== Stability and Reactivity Data =====

Stability Indicator/Materials to Avoid:YES

OXIDIZERS & CORROSIVES

Stability Condition to Avoid:TEMPERATURES OVER 500F & OPEN FLAMES.

Hazardous Decomposition Products:CO*2, CO, OXIDES OF SULFUR &
MOLYBDENUM

Conditions to Avoid Polymerization:WILL NOT POLYMERIZE

===== Disposal Considerations =====

Waste Disposal Methods:PUT CONTAMINATED MATERIAL IN CONTAINERS SUITABLE
FOR SHIPMENT TO

DISPOSAL AREA. INCINERATE OR LANDFILL IAW

APPROPRIATE FEDERAL,STATE & LOCAL REGULATIONS; DO NOT INCINERATE IN
CLOSED OR SEALED CONTAINERS.

Disclaimer (provided with this information by the compiling agencies):

This information is formulated for use by elements of the Department
of Defense. The United States of America in no manner whatsoever,
expressly or implied, warrants this information to be accurate and
disclaims all liability for its use. Any person utilizing this
docume

nt should seek competent professional advice to verify and assume responsibility for the suitability of this information to their particular situation.